



MSR Gold™ SA Double Ended

MSR Gold™ 575 SA/2 DE 1CT/40

To optimize the total lifetime of the double ended MSR Gold™ SA Double Ended lamps, the caps are plated with gold. This provides superior heat protection and thereby minimizes premature failure of the lamp and lamp holder, as well as ensuring extended consistent performance. In addition, the highly innovative P3 technology, developed by Philips, allows the lamp to be used at higher temperatures, which further extends service life and consistency of high-quality light output.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Correlated Colour Temperature (Nom)	
Cap base	SFC-11 [SFC-11]		7500 K
Operating position	UNIVERSAL [Any or Universal (U)]	Luminous efficacy (rated) (nom.)	73 lm/W
Main application	Entertainment	Colour rendering index (nom.)	75
Life to 50% failures (nom.)	750 h	Operating and Electrical	
System description	SA/2 DE	Power (Rated) (Nom)	575 W
Light Technical		Lamp current (nom.)	7 A
Colour Code	2	Ignition supply voltage (min.)	198 V
Luminous flux (min.)	39000 lm	Controls and Dimming	
Luminous flux (nom.)	42000 lm	Dimmable	No
Chromaticity coordinate X (nom.)	294		
Chromaticity coordinate Y (nom.)	317		

MSR Gold™ SA Double Ended

Mechanical and Housing	
Cap-base information	SFc-11
Luminaire Design Requirements	
Pinch temperature (max.)	400 °C
Product Data	
Full product code	872790091464100
Order product name	MSR Gold™ 575 SA/2 DE 1CT/40

EAN/UPC – product	8727900914641
Order code	91464100
SAP numerator – quantity per pack	1
Numerator – packs per outer box	40
SAP material	928175105114
SAP net weight (piece)	0.032 kg



Dimensional drawing



MSR GOLD 575 SA/2 DE

Product	D (max)	O	A (min)	A (max)	A	C (max)
MSR Gold™ 575 SA/2 DE 1CT/40	18.5 mm	5.0 mm	69.6 mm	70.4 mm	70 mm	92 mm

Photometric data



XDPB_XDMSR_575W_SA2-DE-Spectral power distribution B/W

