



MSR Gold™ FastFit

MSR Gold™ 2000 FastFit 1CT/8

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR Gold™ 2000 FastFit can be operated in a lamp wattage range between 800W and 1400W.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General information		Operating and electrical	
Cap base	PGJX50 [PGJX50]	Power (Rated) (Nom)	2000 W
Operating position	UNIVERSAL [Any or Universal (U)]	Lamp current (nom.)	15.2 A
Main application	Entertainment	Ignition supply voltage (min.)	198 V
Life to 50% failures (nom.)	750 h	Chromaticity coordinate Y (nom.)	332
System description	FastFit	Correlated Colour Temperature (Nom)	6050 K
Light technical		Luminous efficacy (rated) (nom.)	90 lm/W
Colour Code	- [Not Specified]	Colour rendering index (nom.)	91
Luminous flux (min.)	162000 lm		
Luminous flux (nom.)	180000 lm		
Chromaticity coordinate X (nom.)	321		

MSR Gold™ FastFit

Controls and dimming

Dimmable	Yes
----------	-----

Mechanical and housing

Cap-base information	PGJX50
----------------------	--------

Luminaire design requirements

Bulb temperature (max.)	950 °C
Pinch temperature (max.)	500 °C

Product data

Full product code	872790091949300
-------------------	-----------------

Order product name	MSR Gold™ 2000 FastFit 1CT/8
EAN/UPC – product	8727900919493
Order code	91949300
SAP numerator – quantity per pack	1
Numerator – packs per outer box	8
SAP material	928176905114
Copy Net Weight (Piece)	0.147 kg

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F
MSR Gold™ 2000 FastFit 1CT/8	34 mm	8.0 mm	66 mm	68 mm	67 mm	134 mm	50 mm

MSR Gold™ 2000 FastFit 1CT/8

