# **PHILIPS** Lighting



# MASTERColour CDM-T Elite

# MASTERC CDM-T Elite 100W/930 G12 1CT/12

Single-ended, high-efficiency Ceramic Metal Halide discharge lamp

#### Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- $\cdot$  The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear. 35W & 70W lamps may also use electromagnetic gear.
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**


General Information		Arc Length O (Nom)	8.5 mm
Cap-Base	G12 [G12]		
Operating Position	UNIVERSAL [Any or Universal (U)]	Operating and Electrical	
Flux measurement reference	Sphere	Power Consumption	100.1 W
ife to 50% Failures (Nom)	20,000 h	Voltage (Nom)	88 V
		Voltage (Nom)	88 V
Light Technical			
Color Code	930 [CCT of 3000K]	Controls and Dimming	
Luminous Flux	11,000 lm	Dimmable	No
olor Designation	Warm White (WW)		
Chromaticity Coordinate X (Nom)	0.434	Mechanical and Housing	
Chromaticity Coordinate Y (Nom)	0.398	Bulb Finish	Clear
Correlated Color Temperature (Nom)	3000 K	Bulb Shape	T19 [T 19mm]
uminous Efficacy (rated) (Nom)	110 lm/W		
Color rendering index (CRI)	92		

## MASTERColour CDM-T Elite

Approval and Application		
Energy Efficiency Class	F	
Mercury (Hg) Content (Max)	10.1 mg	
Mercury (Hg) Content (Nom)	10.1 mg	
Energy Consumption kWh/1000 h	101 kWh	
EPREL Registration Number	473251	
Product Data		
Order product name	MASTERC CDM-T Elite 100W/930 G12 1CT/12	
Full product name	MASTERC CDM-T Elite 100W/930 G12 1CT/12	

Full product code	872790087169200
Order code	928183205125
Material Nr. (12NC)	928183205125
Local order code	CDMTEL100W930
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900871692
Numerator - Packs per outer box	12
EAN/UPC - Case	8727900871708

#### **Dimensional drawing**




# MASTERC CDM-T Elite 100W/930 20 mm 8.5 mm 55 mm 57 mm 56 mm 110 mm G12 1CT/12

D (max) O

Product

#### Photometric data



Light Distribution Diagram - MASTERC CDM-T Elite 100W/930 G12 1CT/12

100 100


Spectral Power Distribution Colour - MASTERC CDM-T Elite 100W/930 G12 1CT/12

C (max)

L(min) L(max) L

## MASTERColour CDM-T Elite

Lifetime



Life Expectancy Diagram - MASTERC CDM-T Elite 100W/930 G12 1CT/12

\$ 100 c

Lumen Maintenance Diagram - MASTERC CDM-T Elite 100W/930 G12 1CT/12



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 14 - data subject to change