



# MASTERColour CDM-R111 Elite

## MASTERC CDM-R111 Elite 35W/930 GX8.5 10D

MASTERColour CDM-R111 Elite combines the trendy look of 111 mm aluminium-reflector halogen lamps with the long life, high energy efficiency and crisp white light of MASTERColour CDM.

#### Warnings and Safety

- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. 35W/930 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

| General Information             |                                  |
|---------------------------------|----------------------------------|
| Cap-Base                        | GX8.5 [GX8.5]                    |
| Operating Position              | UNIVERSAL [Any or Universal (U)] |
| Switching Cycle                 | 1,050                            |
| Flux measurement reference      | Narrow Cone                      |
| Life to 50% Failures (Nom)      | 12,000 hour(s)                   |
|                                 |                                  |
| Light Technical                 |                                  |
| Color Code                      | 930 [CCT of 3000K]               |
| Beam Angle (Nom)                | 10 degree(s)                     |
| Luminous Flux                   | 1,350 lm                         |
| Luminous Intensity (Nom)        | 36,000 cd                        |
| Color Designation               | Warm White (WW)                  |
| Chromaticity Coordinate X (Nom) | 0.434                            |
| Chromaticity Coordinate Y (Nom) | 0.398                            |
| Chromaticity Coordinate Y (Nom) | 0.398                            |

| Correlated Color Temperature (Nom)   | 3000 K   |
|--------------------------------------|----------|
| Luminous Efficacy (rated) (Nom)      | 37 lm/W  |
| Color rendering index (CRI)          | 90       |
| LLMF At End Of Nominal Lifetime (Nom | 70 %     |
| Luminous Flux in 90° Cone (Rated)    | 1,350 lm |
|                                      |          |
| Operating and Electrical             |          |
| Power Consumption                    | 39.1 W   |
| Warm-up time to 60% light            | 120 s    |
| Voltage (Nom)                        | 89 V     |
| Voltage (Nom)                        | 89 V     |
|                                      |          |
| Controls and Dimming                 |          |
| Dimmable                             | No       |
|                                      |          |


Datasheet, 2023, May 15 data subject to change

## **MASTERColour CDM-R111 Elite**

| Mechanical and Housing        |  |  |
|-------------------------------|--|--|
| Bulb Finish                   | Reflector                                |  |
| Bulb Shape                    | R111 [R 111mm]                           |  |
|                               |  |  |
| Approval and Application      |  |  |
| Energy Efficiency Class       | G  |  |
| Mercury (Hg) Content (Max)    | 4.7 mg                                   |  |
| Mercury (Hg) Content (Nom)    | 4.7 mg                                   |  |
| Energy Consumption kWh/1000 h | 40 kWh                                   |  |
| EPREL Registration Number     | 473279                                   |  |
|                               |  |  |
| Product Data                  |  |  |
| Order product name            | MASTERC CDM-R111 Elite 35W/930 GX8.5 10D |  |


| Full product name               | MASTERC CDM-R111 Elite 35W/930 GX8.5 10D |
|---------------------------------|--|
| Full product code               | 871829168918800                          |
| Order code                      | 928195305330                             |
| Material Nr. (12NC)             | 928195305330                             |
| Numerator - Quantity Per Pack   | 1  |
| EAN/UPC - Product/Case          | 8718291689188                            |
| Numerator - Packs per outer box | 6  |
| EAN/UPC - Case                  | 8718291689195                            |
|                                 |  |

#### Dimensional drawing




| Product                                  | D (max) | C (max) |
|--|---------|---------|
| MASTERC CDM-R111 Elite 35W/930 GX8.5 10D | 111 mm  | 95 mm   |

#### Photometric data







Light Distribution Diagram - MASTERC CDM-R111 Elite 35W/930 GX8.5 10D

## **MASTERColour CDM-R111 Elite**



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.