



MASTER SON-T PIA Plus

MST SON-T PIA Plus 100W E40 1SL/12

High Pressure Sodium lamp with clear tubular outer bulb, high output and long reliable lifetime

Warnings and Safety

- Control gear must include end-of-life protection (IEC60662, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


| General Information | | Voltage (Nom) | 100 V |
|------------------------------------|----------------------------------|-------------------------------|---------|
| Cap-Base | E40 | Voltage (Nom) | 100 V |
| Operating Position | UNIVERSAL [Any or Universal (U)] | | |
| Flux measurement reference | Sphere | Controls and Dimming | |
| Life to 50% Failures (Nom) | 28000 hour(s) | Dimmable | Yes |
| Light Technical | | Mechanical and Housing | |
| Color Code | 220 [CCT of 2000K] | Bulb Finish | Clear |
| Luminous Flux | 10600 lm | Bulb Shape | T46 |
| Chromaticity Coordinate X (Nom) | 0.535 | | |
| Chromaticity Coordinate Y (Nom) | 0.42 | Approval and Application | |
| Correlated Color Temperature (Nom) | 2000 K | Energy Efficiency Class | F |
| Luminous Efficacy (rated) (Nom) | 105 lm/W | Mercury (Hg) Content (Max) | 16.3 mg |
| Color rendering index (CRI) | - | Mercury (Hg) Content (Nom) | 14.3 mg |
| | | Energy Consumption kWh/1000 h | 101 kWh |
| Operating and Electrical | | EPREL Registration Number | 473289 |
| Power Consumption | 101.0 W | | |

MASTER SON-T PIA Plus

| Product Data | |
|---------------------|------------------------------------|
| Order product name | MST SON-T PIA Plus 100W E40 1SL/12 |
| Full product name | MST SON-T PIA Plus 100W E40 1SL/12 |
| Full product code | 871829118071500 |
| Order code | 928483300095 |
| Material Nr. (12NC) | 928483300095 |


| Numerator - Quantity Per Pack | 1 |
|---------------------------------|---------------|
| EAN/UPC - Product/Case | 8718291180715 |
| Numerator - Packs per outer box | 12 |
| EAN/UPC - Case | 8718291180722 |

Dimensional drawing




| Product | D (max) | 0 | L | C (max) |
|------------------------------------|---------|-------|--------|---------|
| MST SON-T PIA Plus 100W E40 1SL/12 | 47 mm | 47 mm | 132 mm | 209 mm |

Photometric data





Light Distribution Diagram - MST SON-T PIA Plus 100W E40 1SL/12



Spectral Power Distribution Colour - MST SON-T PIA Plus 100W E40 1SL/12







Life Expectancy Diagram

MASTER SON-T PIA Plus



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 16 - data subject to change