

MASTER SON-T PIA Plus

MST SON-T PIA Plus 150W E40 1SL/12

High Pressure Sodium lamp with clear tubular outer bulb, high output and long reliable lifetime

Warnings and Safety

- Control gear must include end-of-life protection (IEC60662, IEC 62035)
- Control gear must include end-of-life protection (IEC60662, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	E40 [E40]
Operating Position	UNIVERSAL [Any or Universal (U)]
Flux measurement reference	Sphere
Life to 50% Failures (Nom)	32,000 hour(s)

Light Technical	
Color Code	220 [CCT of 2000K]
Luminous Flux	17,800 lm
Chromaticity Coordinate X (Nom)	0.535
Chromaticity Coordinate Y (Nom)	0.42
Correlated Color Temperature (Nom)	2000 K
Luminous Efficacy (rated) (Nom)	115 lm/W
Color rendering index (CRI)	-

Operating and Electrical	
Power Consumption	155.0 W
Voltage (Nom)	100 V
Voltage (Nom)	100 V

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Clear

MASTER SON-T PIA Plus

Bulb Shape	T46 [T 46mm]

Full product name	MST SON-T PIA Plus 150W E40 1SL/12
Full product code	871829118073900
Order code	928483400095
Material Nr. (12NC)	928483400095
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291180739
Numerator - Packs per outer box	12
EAN/UPC - Case	8718291180746


Approval and Application

Energy Efficiency Class	F
Mercury (Hg) Content (Max)	15.1 mg
Mercury (Hg) Content (Nom)	13.9 mg
Energy Consumption kWh/1000 h	155 kWh
EPREL Registration Number	473290

Product Data


Order product name	MST SON-T PIA Plus 150W E40 1SL/12

Dimensional drawing





Product	D (max)	O	L	C (max)
MST SON-T PIA Plus 150W E40 1SL/12	47 mm	61 mm	132 mm	209 mm

Photometric data



Light Distribution Diagram - MST SON-T PIA Plus 150W E40 1SL/12







Spectral Power Distribution Colour - MST SON-T PIA Plus 150W E40 1SL/12

MASTER SON-T PIA Plus

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.