



SON

SON 250W E E40 CO 1SL

High Pressure Sodium lamp with opalized ovoid outer bulb

Warnings and Safety


- Control gear must include end-of-life protection (IEC60662, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	E40
Operating Position	UNIVERSAL [Any or Universal (U)]
Life to 50% Failures (Nom)	28,000 hour(s)
Light Technical	
Color Code	220 [CCT of 2000K]
Correlated Color Temperature (Nom)	2000 K
Luminous Efficacy (rated) (Nom)	106 lm/W
Operating and Electrical	
Power Consumption	250 W
Voltage (Nom)	100 V
Voltage (Nom)	100 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Coated glass



Bulb Shape	ED90
Approval and Application	
Mercury (Hg) Content (Nom)	20.4 mg
Energy Consumption kWh/1000 h	275 kWh
Product Data	
Order product name	SON 250W E E40 CO 1SL
Full product name	SON 250W E E40 CO 1SL
Full product code	872790090667700
Order code	928486900097
Material Nr. (12NC)	928486900097
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900906677
Numerator - Packs per outer box	12
EAN/UPC - Case	8727900906684

Dimensional drawing



Product	D (max)	C (max)
SON 250W E E40 CO 1SL	91 mm	226 mm



Photometric data



Light Distribution Diagram - SON 250W E E40 CO 1SL

Spectral Power Distribution Colour - SON 250W E E40 CO 1SL

Lifetime



Life Expectancy Diagram - SON 250W E E40 CO 1SL

Lumen Maintenance Diagram - SON 250W E E40 CO 1SL

SON

