



MASTERCcolour CDM MW Eco

MASTERCcolour MW eco MASTERCcolour CDM-EP MW eco 360W/840 E40

Ceramic metal halide lamps with clear tubular or coated ellipsoid outer bulb, tailor-made to replace and outperform quartz metal halide lamps on existing gear.

Product data

General Information	
Cap base	E40 [E40]
Operating position	UNIVERSAL [Any/Universal]
Life to 20% failures (nom.)	12000 h
Life to 50% failures (nom.)	20000 h
System description	Universal
LSF 2000 h Rated	99 %
LSF 4000 h Rated	96 %
LSF 8000 h Rated	88 %
LSF 12000 h Rated	80 %
LSF 16000 h Rated	63 %
LSF 20000 h Rated	50 %
Light Technical	
Colour code	840 [CCT of 4,000 K]
Luminous flux (rated) (nom.)	35000 lm
Colour designation	Cool White (CW)
Chromaticity coordinate X (nom.)	386
Chromaticity coordinate Y (nom.)	395
Correlated colour temperature (nom.)	4000 K
Luminous efficacy (rated) (nom.)	97 lm/W

Color rendering index (nom.)	90
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	84 %
LLMF 8000 h Rated	82 %
LLMF 12000 h Rated	80 %
LLMF 16000 h Rated	77 %
LLMF 20000 h Rated	75 %

Operating and Electrical	
Power (Rated) (Nom)	360 W
Lamp current run-up (max.)	3.6 A
Lamp current (EM) (nom.)	3.55 A
Re-ignition time (min.) (max.)	900 s
Ignition time (max.)	30 s
Voltage (Max)	127 V
Voltage (Min)	109 V
Voltage (Nom)	118 V

MASTERColour CDM MW Eco

Controls and Dimming

Run-up time 90% (max.)	3 min
------------------------	-------

Mechanical and Housing

Bulb finish	Clear
Bulb material	Hard Glass

Approval and Application

Energy efficiency label (EEL)	A+
Mercury (Hg) content (nom.)	44.6 mg
Energy Consumption kWh/1000 h	396 kWh

UV

PET (NIOSH) (nom.)	8 h/500lx
--------------------	-----------

Luminaire Design Requirements

Bulb temperature (max.)	350 °C
-------------------------	--------

Cap base temperature (max.)	250 °C
-----------------------------	--------


Product Data

Full product code	871869673481000
Order product name	MASTERColour MW eco MSTColour CDM-EP MW eco 360W/840 E40 CL
EAN/UPC – product	8718696734810
Order code	73481000
Numerator – quantity per pack	1
Numerator – packs per outer box	6
Material no. (12NC)	928495409891
Net weight (piece)	259.000 g

Warnings and Safety

- For use with control gear designed for high-pressure mercury or high-pressure sodium lamps with an external ignitor
- A lamp breaking is extremely unlikely to have an impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Warm restart time can be up to 15 minutes; T15 ignitors therefore advised.

Dimensional drawing



CDM-EP MW Eco 360W E40

Product	D (max)	C (max)
MASTERColour MW eco MSTColour CDM-EP MW eco 360W/840 E40 CL	121 mm	290 mm

