



Ceramalux ALTO Non-Cycling

C250S50/ALTO NC HPS 1/12PK

Philips Ceramalux High Pressure Sodium Non-Cycling Lamps are a better value than standard high pressure sodium lamps, with longer life and reduced maintenance cost.

Product data


General Information			
Cap-Base	E39 [Single Contact Mogul Screw]		
Operating Position	UNIVERSAL [Any or Universal (U)]		
Features	ALTO® Non-Cycling		
Light Technical			
Chromaticity Coordinate X (Nom)	0.523		
Chromaticity Coordinate Y (Nom)	0.415		
Correlated Color Temperature (Nom)	2100 K		
Luminous Efficacy (Rated) (Min)	102 lm/W		
Luminous Efficacy (rated) (Nom)	114 lm/W		
Color rendering index (CRI)	21		
Operating and Electrical			
Power Consumption	251 W		
Lamp Current (Nom)	1.8 A		
Voltage (Nom)	100 V		
Voltage (Nom)	100 V		

Mechanical and Housing			
Bulb Finish	Clear		
Bulb Material	Hard Glass		
Bulb Shape	ED18		
Approval and Application			
Mercury (Hg) Content (Nom)	3.36 mg		
Product Data			
Order product name	C250S50/ALTO NC HPS 1/12PK		
Full product name	C250S50/ALTO NC HPS 1/12PK		
Order code	928601156190		
Material Nr. (12NC)	928601156190		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	046677467340		
Numerator - Packs per outer box	12		
EAN/UPC - Case	50046677467345		

Datasheet, 2024, February 1 data subject to change

Ceramalux ALTO Non-Cycling

Dimensional drawing



Product	D	L	C (max)
C250S50/ALTO NC HPS 1/12PK	2.25 inch	5.750 inch	9.75 inch



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.