



LED PAR38

120V PAR38 17W 25D 3000K 1200 D AF SO

Philips LED spots with a single optic beam, provide a clean beam that's free from shadows with beam angles from 15 and 40 degrees to suit every general lighting application.

Product data


General Information		Wattage Equivalent	
Cap-Base	E26 [Single Contact Medium Screw]	120 W	
Nominal lifetime	25,000 hour(s)	Starting Time (Nom)	
Switching Cycle	50,000	0.5 s	
Lighting Technology	LED	Warm-up time to 60% light	
EU RoHS compliant	Yes	0.5 s	
Light Technical		Power Factor (Fraction)	
Color Code	830 [CCT of 3000K]	0.85	
Beam Angle (Nom)	25 degree(s)	Voltage (Nom)	
Luminous Flux	1,250 lm	120 V	
Luminous Intensity (Nom)	7,100 cd	Temperature	
Color Designation	White (WH)	T-Case Maximum (Nom)	
Correlated Color Temperature (Nom)	3000 K	89 °C	
Luminous Efficacy (rated) (Nom)	74 lm/W	Controls and Dimming	
Color Consistency	<6	Dimmable	
Color rendering index (CRI)	80	Yes	
LLMF At End Of Nominal Lifetime (Nom)	70 %	Mechanical and Housing	
Operating and Electrical		Bulb Shape	
Line Frequency	60 Hz	PAR38 [PAR 4.75 inch/121mm]	
Input Frequency	60 Hz	Approval and Application	
Power Consumption	17 W	Suitable For Accent Lighting	
Lamp Current (Nom)	167 mA	Yes	
		Energy Certifications	
		Energy Star	
		Product Data	
		Order product name	
		120V PAR38 17W 25D 3000K 1200 D AF SO	
		Full product name	
		120V PAR38 17W 25D 3000K 1200 D AF SO	
		Order code	
		929001113504	
		Material Nr. (12NC)	
		929001113504	

LED PAR38

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677435394
Numerator - Packs per outer box	6


EAN/UPC - Case	50046677435399
----------------	----------------

Dimensional drawing




Product	D	C
120V PAR38 17W 25D 3000K 1200 D AF SO	120.3 mm	130.5 mm

Photometric data



Spectral Power Distribution Colour - 120V PAR38 17W 25D 3000K 1200 D AF SO

Light Distribution Diagram - 120V PAR38 17W 25D 3000K 1200 D AF SO



General uniform lighting - 120V PAR38 17W 25D 3000K 1200 D AF SO

LED PAR38

