



CorePro LEDcapsule LV

CorePro LEDcapsuleLV 1.2-10W 830 G4

The CorePro LEDcapsule is a true alternative to the halogen capsule. It is particularly suitable for task lighting and decorative applications in homes, shops, hotels and restaurants. Compatible with existing fixtures with G4 holders and designed for retrofit replacement of halogen capsules, CorePro LEDcapsule delivers huge energy savings and minimizes maintenance costs without any compromise on light quality.

Product data


General Information		Power Consumption	
Cap-Base	G4 [G4]	1.2 W	
Nominal lifetime	15,000 hour(s)	Lamp Current (Nom)	
Switching Cycle	50,000	200 mA	
Lighting Technology	LED	Wattage Equivalent	
EU RoHS compliant	Yes	10 W	
Light Technical		Starting Time (Nom)	
Color Code	830 [CCT of 3000K]	0.5 s	
Luminous Flux	105 lm	Warm-up time to 60% light	
Color Designation	White (WH)	0.5 s	
Correlated Color Temperature (Nom)	3000 K	Power Factor (Fraction)	
Luminous Efficacy (rated) (Nom)	87.5 lm/W	0.5	
Color Consistency	<6	Voltage (Nom)	
Color rendering index (CRI)	80	12 V	
LLMF At End Of Nominal Lifetime (Nom)	70 %	Controls and Dimming	
Operating and Electrical		Dimmable	
Line Frequency	50 to 60 Hz	No	
Input Frequency	50 to 60 Hz	Mechanical and Housing	
		Bulb Shape	
		Capsule	
		Approval and Application	
		Energy Consumption kWh/1000 h	
		2 kWh	
		Product Data	
		Order product name	
		CorePro LEDcapsuleLV 1.2-10W 830 G4	
		Full product name	
		CorePro LEDcapsuleLV 1.2-10W 830 G4	

CorePro LEDcapsule LV

Full product code	871869642228100
Order code	929001118702
Material Nr. (12NC)	929001118702
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696422281


Numerator - Packs per outer box	12
EAN/UPC - Case	8718696422298

Dimensional drawing



Product	D	C
CorePro LEDcapsuleLV 1.2-10W 830 G4	14.3 mm	39.2 mm

Photometric data



Light Distribution Diagram - CorePro LEDcapsuleLV 1.2-10W 830 G4

Spectral Power Distribution Colour - CorePro LEDcapsuleLV 1.2-10W 830 G4

