PHILIPS

Lighting

# Essential LEDtube

## LEDtube 1200mm 16W 765 T8 CN I

Essential LEDtube is an affordable LED tube that is suitable for replacing T8 fluorescent lamps. The product provides a natural lighting effect for use in general lighting applications, as well as instant energy savings – an environmentally friendly solution.

### Product data

| General Information | |
|---|---|
| **Cap-Base** | G13 [Medium Bi-Pin Fluorescent] |
| **Nominal lifetime** | 15,000 hour(s) |
| **Switching Cycle** | 50,000 |
| **Lighting Technology** | LED |
| **EU RoHS compliant** | Yes |

| Light Technical | |
|---|---|
| **Color Code** | 765 [CCT of 6500K] |
| **Beam Angle (Nom)** | 240 degree(s) |
| **Luminous Flux** | 1,600 lm |
| **Color Designation** | Cool Daylight |
| **Correlated Color Temperature (Nom)** | 6500 K |
| **Luminous Efficacy (rated) (Nom)** | 100.00 lm/W |
| **Color Consistency** | <6 |
| **Color rendering index (CRI)** | 73 |
| **LLMF At End Of Nominal Lifetime (Nom)** | 70 % |

| Operating and Electrical | |
|---|---|
| **Line Frequency** | 50 to 60 Hz |
| **Input Frequency** | 50 to 60 Hz |
| **Power Consumption** | 16 W |
| **Starting Time (Nom)** | 0.5 s |
| **Warm-up time to 60% light** | 0.5 s |
| **Power Factor (Fraction)** | 0.5 |
| **Voltage (Nom)** | 220-240 V |

| Temperature | |
|---|---|
| **Ambient temperature range** | -20 °C to 45 °C |
| **T-Case Maximum (Nom)** | 60 °C |

| Controls and Dimming | |
|---|---|
| **Dimmable** | No |

| Mechanical and Housing | |
|---|---|
| **Product Length** | 1,200 mm |
| **Bulb Shape** | T8 |

| Approval and Application | |
|---|---|
| **Energy Saving Product** | Yes |
| **Suitable For Accent Lighting** | No |
| **Approval Marks** | RoHS compliance KEMA Keur certificate |
| **Energy Consumption kWh/1000 h** | 16 kWh |

| Product Data | |
|---|---|
| **Order product name** | LEDtube 1200mm 16W 765 T8 CN I |

# Essential LEDtube

| | |
|---|---|
| **Full product name** | LEDtube 1200mm 16W 765 T8 CN I |
| **Full product code** | 694793910548900 |
| **Order code** | 929001127510 |
| **Material Nr. (12NC)** | 929001127510 |
| **Numerator - Quantity Per Pack** | 1 |

| | |
|---|---|
| **EAN/UPC - Product/Case** | 6947939105489 |
| **Numerator - Packs per outer box** | 25 |
| **EAN/UPC - Case** | 6947939105496 |

## Dimensional drawing




| Product | D1 | D2 | A1 | A2 | A3 |
|---|---|---|---|---|---|
| LEDtube 1200mm 16W 765 T8 CN I | 25.68 mm | 28 mm | 1,198.0 mm | 1,205.0 mm | 1,212.0 mm |

## Photometric data



General uniform lighting - LEDtube 1200mm 16W 765 T8 CN I




Light Distribution Diagram - LEDtube 1200mm 16W 765 T8 CN I




Spectral Power Distribution Colour - LEDtube 1200mm 16W 765 T8 CN I

## Lifetime







**Life Expectancy Diagram - LEDtube 1200mm 16W 765 T8 CN I**

**Life Expectancy Diagram - LEDtube 1200mm 16W 765 T8 CN I**







**Lumen Maintenance Diagram - LEDtube 1200mm 16W 765 T8 CN I**

**Life Expectancy Diagram - LEDtube 1200mm 16W 765 T8 CN I**




**Lumen Maintenance Diagram**

## Essential LEDtube

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com
2023, May 15 - data subject to change