



# MASTER VALUE LEDspot MV

## MAS LEDspotMV D 5.4-50W GU10 927 25D

Delivering a warm, halogen-like accent beam, MASTER VALUE is a perfect fit for spot lighting. Thanks to its high CRI, it realizes more natural colors, creating cozy and comfortable ambiances for residential and hospitality projects, and emphasizing the beauty of merchandise in retail. These LED spots MV GU10 have the familiar look and feel of spot lamps, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables you to create the atmosphere you desire, and it works with broad selection of dimmers. MASTER VALUE also offers more energy savings than normal LED spots.

### Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

### Product data

General Information	
Cap-Base	GU10 [GU10]
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	927
Beam Angle (Nom)	25 degree(s)
Luminous Flux	395 lm

Luminous Intensity (Nom)	1,350 cd
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	66.67 lm/W
Color Consistency	<6
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	360 lm
Operating and Electrical	
Line Frequency	50 to 60 Hz

# MASTER VALUE LEDspot MV

Input Frequency	50 to 60 Hz
Power Consumption	5.4 W
Lamp Current (Nom)	28 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	0.85
Voltage (Nom)	220-240 V

## Temperature

T-Case Maximum (Nom)	91 °C
----------------------	-------

## Controls and Dimming

Dimmable	Yes
----------	-----

## Mechanical and Housing

Bulb Shape	PAR16 [PAR 2 inch/50mm]
------------	-------------------------


## Approval and Application

Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	6 kWh

## Product Data


Order product name	MAS LEDspotMV D 5.4-50W GU10 927 25D
Full product name	MAS LEDspotMV D 5.4-50W GU10 927 25D
Full product code	871869645715300
Order code	929001138602
Material Nr. (12NC)	929001138602
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696457153
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696457160

## Dimensional drawing




Product	D	C
MAS LEDspotMV D 5.4-50W GU10 927 25D	50 mm	57 mm

## Photometric data



Light Distribution Diagram - MAS LEDspotMV D 5.4-50W GU10 927 25D



Spectral Power Distribution Colour - MAS LEDspotMV D 5.4-50W GU10 927 25D

## MASTER VALUE LEDspot MV

