



# MASTER Plastic LEDcandles & lusters

# MAS LEDcandle DT 4-25W E14 B38 CL\_AP

Delivering incandescent-like sparkling light effects, MASTER LEDcandle bulbs are ideal for general and decorative lighting in the hospitality industry, as well as in home environments. The dimmable MASTER LEDcandles drive further efficiencies, while helping to create the desired atmosphere. Mounted in full view in chandeliers, wall scones or modern luminaires, the clear or frosted glass bulbs fit all existing fixtures with an E14 and B15 socket. Drawing upon inputs from chandelier makers and designed to enhance the aesthetic appeal of the chandelier or luminaire, not only when lit but also when not, these lamps come in a classical slender shape with a unique, eye-catching lens design. They produce a beautiful sparkling warm light that delivers huge energy savings and minimizes maintenance cost. The flame-shaped candle lamps comes in a classical slender shape with a unique, eye-catching lens design that perfectly complements modern LED candles.

### **Product data**

General Information		
Cap-Base	E14	
Nominal lifetime	25,000 hour(s)	
Switching Cycle	50,000	
Lighting Technology	LED	
EU RoHS compliant	Yes	
Light Technical		
Color Code	822-827 [tunable warm white]	
Luminous Flux	250 lm	
Color Designation	Warm White (WW)	
Luminous Efficacy (rated) (Nom)	65 lm/W	
Color Consistency	<6	

Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	4 W
Lamp Current (Nom)	25 mA
Wattage Equivalent	25 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	0.7


Datasheet, 2023, April 14 data subject to change

## **MASTER Plastic LEDcandles & lusters**

Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	85 ℃
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	B38
Approval and Application	
Suitable For Accent Lighting	No


Energy Consumption kWh/1000 h	4 kWh	
Product Data		
Order product name	MAS LEDcandle DT 4-25W E14 B38 CL_AP	
Full product name	MAS LEDcandle DT 4-25W E14 B38 CL_AP	
Full product code	871869645372800	
Order code	929001139808	
Material Nr. (12NC)	929001139808	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8718696453728	
Numerator - Packs per outer box	10	
EAN/UPC - Case	8718696453735	

## Dimensional drawing




Product	D	С
MAS LEDcandle DT 4-25W E14 B38 CL_AP	38 mm	113 mm

## Photometric data



Light Distribution Diagram - MAS LEDcandle DT 4-25W E14 B38 CL\_AP



Spectral Power Distribution Colour - MAS LEDcandle DT 4-25W E14 B38 CL\_AP

## **MASTER Plastic LEDcandles & lusters**



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.