



MASTER LEDspot LV

MAS LEDspotLV D 8.0-50W 830 MR16 24D

Delivering intense accent beam, MASTER LEDspot LV is an ideal retrofit solution for spot lighting. MASTER LEDspot LV is designed to replace halogen or incandescent spots. It realizes natural colors, enables cozy and comfortable ambience for residential, hospitality and emphasizes the beauty of merchandise in retail. New smaller housing provides perfect fitting with majority of luminaires in a market with a MR16 GU 5.3 holder. It not only employs Philips' patented solution to guarantee the broadest possible compatibility with standard 12V halogen electronic transformers, it also delivers high beam intensity which is equivalent to halogen MR16 spots. The dimming function enables to create the desired atmosphere and it works with broad selection of dimmers. Its high SDCM ensure stricter color consistency, that is maintained over product life. MASTER LEDspot LV delivers huge energy savings and minimizes maintenance cost without any compromise on light quality and lifetime, enabling residential and business owners to achieve a return on their investment within short period time.

Product data

General Information	
Cap-Base	GU5.3 [GU5.3]
Nominal lifetime	40,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	24 degree(s)
Luminous Flux	660 lm
Luminous Intensity (Nom)	3,250 cd
Color Designation	White (WH)

Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	78 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	621 lm
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	8 W

900 mA

Datasheet, 2023, April 29 data subject to change


Lamp Current (Nom)
Wattage Equivalent

MASTER LEDspot LV

Starting Time (Nom)	0.5 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	0.7
Voltage (Nom)	12 V
Temperature	
T-Case Maximum (Nom)	105 ℃
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Shape	MR16 [2inch/50mm]
Approval and Application	
Suitable For Accent Lighting	Yes


Energy Consumption kWh/1000 h	9 kWh	
EyeComfort	Yes	
Product Data		
Order product name	MAS LEDspotLV D 8.0-50W 830 MR16 24D	
Full product name	MAS LEDspotLV D 8.0-50W 830 MR16 24E	
Full product code	871869649001300	
Order code	49001300	
Material Nr. (12NC)	929001149902	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8718696490013	
Numerator - Packs per outer box	10	
EAN/UPC - Case	8718696490020	

Dimensional drawing



Product	D	С
MAS LEDspotLV D 8.0-50W 830 MR16 24D	51 mm	55 mm

Photometric data





Light Distribution Diagram - MAS LEDspotLV D 8.0-50W 830 MR16 24D

Spectral Power Distribution Colour - MAS LEDspotLV D 8.0-50W 830 MR16 24D

MASTER LEDspot LV



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.