

MASTER Plastic LEDbulbs

MAS LEDbulb DT 6-40W B22 A60 CL

MASTER LEDbulb range delivers a dimmable glow effect for a welcoming, warm atmosphere, making it ideal for general lighting applications in the hospitality industry. Its unique design radiates warm light in all directions, making it a true alternative to the incandescent lamp. It is particularly suitable for public areas such as lobbies, corridors, stairwells, where the light is always on. Compatible with existing fixtures with an E27 or a B22 holder and designed for retrofit replacement of incandescent bulbs, MASTER LEDbulb delivers huge energy savings and minimises maintenance cost without any compromise on light quality.

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

Product data

General Information	
Cap-Base	B22 [B22]
Nominal lifetime	25000 hour(s)
Switching Cycle	50000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	822-827 [tunable warm white]
Luminous Flux	470 lm
Color Designation	Warm White (WW)
Luminous Efficacy (rated) (Nom)	78.00 lm/W
Color Consistency	<lt/>6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	6 W
Lamp Current (Nom)	37 mA
Wattage Equivalent	40 W

MASTER Plastic LEDbulbs

Starting Time (Nom)	0.5 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	0.7
Voltage (Nom)	220-240 V

Temperature

T-Case Maximum (Nom)	85 °C

Controls and Dimming

Dimmable	Yes

Mechanical and Housing

Bulb Finish	Clear
Bulb Shape	A60 [A 60mm]

Approval and Application


Suitable For Accent Lighting	No

Energy Consumption kWh/1000 h	6 kWh
EyeComfort	Yes


Product Data

Order product name	MAS LEDbulb DT 6-40W B22 A60 CL
Full product name	MAS LEDbulb DT 6-40W B22 A60 CL
Full product code	871869648130100
Order code	929001150602
Material Nr. (12NC)	929001150602
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696481301
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696481318

Dimensional drawing




Product	D	C
MAS LEDbulb DT 6-40W B22 A60 CL	60 mm	110 mm



Product
MAS LEDbulb DT 6-40W B22 A60 CL

MASTER Plastic LEDbulbs

Photometric data



Light Distribution Diagram - MAS LEDbulb DT 6-40W B22 A60 CL



Spectral Power Distribution Colour - MAS LEDbulb DT 6-40W B22 A60 CL

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.