



# MASTER VALUE LEDs

## pot LV

### MASTER LEDspotLV VLE D6.3-35W 830MR16 36DRN

Delivering a warm, halogen-like accent beam, MASTER LEDspot LV is an ideal retrofit solution for spot and general lighting applications in the hospitality industry. It is particularly suited to public areas such as receptions, lobbies, corridors, stairwells and washrooms, where the light is on all the time. The robustly designed MASTER LEDspot offers a choice of beam angles for a clearly defined beam spread. There is no UV or IR in the beam, making it suitable for illuminating heat-sensitive objects (food, organic materials, paintings, etc.). The patented intelligent driver enables broad compatibility with existing electromagnetic and electronic halogen transformers. The dimmable versions drive further efficiencies, while helping to create the desired atmosphere.

#### Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

#### Product data

General Information		Light Technical	
Cap-Base	GU5.3 [GU5.3]	Color Code	830 [CCT of 3000K]
Nominal lifetime	25,000 hour(s)	Beam Angle (Nom)	36 degree(s)
Switching Cycle	50,000	Luminous Flux	395 lm
Lighting Technology	LED	Luminous Intensity (Nom)	1,000 cd
EU RoHS compliant	Yes	Color Designation	White (WH)
		Correlated Color Temperature (Nom)	3000 K
		Luminous Efficacy (rated) (Nom)	63 lm/W

MASTER VALUE LEDspot LV

Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	395 lm

Operating and Electrical

Power Consumption	6.3 W
Lamp Current (Nom)	800 mA
Wattage Equivalent	35 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	0.7
Voltage (Nom)	12 V

Temperature

T-Case Maximum (Nom)	100 °C
----------------------	--------

Controls and Dimming

Dimmable	Yes
----------	-----

Mechanical and Housing

Bulb Shape	MR16 [2inch/50mm]
------------	-------------------


Approval and Application

Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	7 kWh

Product Data

Order product name	MAS LEDspotLV VLE D6.3-35W 830MR16 36DRN
Full product name	MASTER LEDspotLV VLE D6.3-35W 830MR16 36DRN
Full product code	871869649029700
Order code	49029700
Material Nr. (12NC)	929001152202
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696490297
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696490303


Dimensional drawing



Product	D	C
MAS LEDspotLV VLE D6.3-35W 830MR16 36DRN	51 mm	51 mm

MASTER VALUE LEDspot LV

Photometric data



Light Distribution Diagram - MAS LEDspotLV VLE D6.3-35W 830MR16 36DRN

Spectral Power Distribution Colour - MAS LEDspotLV VLE D6.3-35W 830MR16 36DRN

