



# MASTER LEDspot LV

## MASTER LED 7-50W 940 MR16 36D Dim

Delivering intense accent beam, MASTER LEDspot LV is an ideal retrofit solution for spot lighting. MASTER LEDspot LV is designed to replace halogen or incandescent spots. It realizes natural colors, enables cozy and comfortable ambience for residential, hospitality and emphasizes the beauty of merchandise in retail. New smaller housing provides perfect fitting with majority of luminaires in a market with a MR16 GU 5.3 holder. It not only employs Philips' patented solution to guarantee the broadest possible compatibility with standard 12V halogen electronic transformers, it also delivers high beam intensity which is equivalent to halogen MR16 spots. The dimming function enables to create the desired atmosphere and it works with broad selection of dimmers. Its high SDCM ensure stricter color consistency, that is maintained over product life. MASTER LEDspot LV delivers huge energy savings and minimizes maintenance cost without any compromise on light quality and lifetime, enabling residential and business owners to achieve a return on their investment within short period time.

### Product data

General Information			
Cap-Base	GU5.3 [GU5.3]	Correlated Color Temperature (Nom)	4000 K
Nominal lifetime	40,000 hour(s)	Luminous Efficacy (rated) (Nom)	57.14 lm/W
Switching Cycle	50,000	Color Consistency	<6
Lighting Technology	LED	Color rendering index (CRI)	90
EU RoHS compliant	Yes	LLMF At End Of Nominal Lifetime (Nom)	70 %
		Luminous Flux in 90° Cone (Rated)	425 lm
Light Technical		Operating and Electrical	
Color Code	940 [CCT of 4000K]	Power Consumption	7 W
Beam Angle (Nom)	36 degree(s)	Lamp Current (Nom)	720 mA
Luminous Flux	460 lm	Wattage Equivalent	50 W
Luminous Intensity (Nom)	1,250 cd	Starting Time (Nom)	0.5 s
Color Designation	Cool White (CW)	Warm-up time to 60% light	1 s

## MASTER LEDspot LV

Power Factor (Fraction)	0.7
Voltage (Nom)	12 V

## Temperature

T-Case Maximum (Nom)	92 °C
----------------------	-------

## Controls and Dimming

Dimmable	Yes
----------	-----

## Mechanical and Housing

Bulb Shape	MR16 [2inch/50mm]
------------	-------------------

## Approval and Application

Energy Saving Product	Yes
-----------------------	-----

Suitable For Accent Lighting	Yes
------------------------------	-----

Energy Consumption kWh/1000 h	8 kWh
-------------------------------	-------

## Product Data

Order product name	MASTER LED 7-50W 940 MR16 36D Dim
--------------------	-----------------------------------

Full product name	MASTER LED 7-50W 940 MR16 36D Dim
-------------------	-----------------------------------

Full product code	871869667342300
-------------------	-----------------

Order code	929001153338
------------	--------------

Material Nr. (12NC)	929001153338
---------------------	--------------


Numerator - Quantity Per Pack	1
-------------------------------	---

EAN/UPC - Product/Case	8718696673423
------------------------	---------------

Numerator - Packs per outer box	10
---------------------------------	----



EAN/UPC - Case	8718696673430
----------------	---------------

## Dimensional drawing



Product	D	C
MASTER LED 7-50W 940 MR16 36D Dim	51 mm	51 mm

### Photometric data



CaluLaX Photometrics 4.2 Philips Lighting B.V. Page 1/1

**Light Distribution Diagram - MASTER LED 7-50W 940 MR16 36D Dim**

General uniform lighting - MASTER LED 7-50W 940 MR16 36D Dim

## MASTER LEDspot LV

### Photometric data



Spectral Power Distribution Colour - MASTER LED 7-50W 940 MR16 36D

Dim

