



CorePro LEDspot MV

CorePro LEDspotMV 5-50W GU10 830 36D RN

CorePro LEDspots are a perfect fit for spot lighting and deliver warm halogen-like light. They are compatible with most existing fixtures with a GU10 or E14 holder and are designed as a retrofit replacement for halogen or incandescent spots. LEDlamps deliver huge energy savings and minimize maintenance cost.

Product data

General Information	
Cap base	GU10 [GU10]
Nominal lifetime (nom.)	15000 h
Switching cycle	50000X
Technical type	5-50W
Light Technical	
Colour code	830 [CCT of 3,000 K]
Beam Angle (Nom)	36 °
Light distribution	36D [Medium beam]
Luminous flux (nom.)	390 lm
Luminous flux (rated) (nom.)	390 lm
Luminous intensity (nom.)	900 cd
Colour designation	White (WH)
Rated beam angle	36 °
Correlated colour temperature (nom.)	3000 K
Luminous efficacy (rated) (nom.)	70.00 lm/W
Colour consistency	<6
Colour rendering index (nom.)	80
LLMF at end of nominal lifetime (nom.)	70 %
Luminous Flux in 90° Cone (Rated)	350 lm

Operating and Electrical	
Input frequency	50 to 60 Hz
Power (Rated) (Nom)	5 W
Lamp current (nom.)	40 mA
Starting time (nom.)	0.5 s
Warm-up time to 60% light (nom.)	instant full light
Power factor (nom.)	0.5
Voltage (Nom)	220-240 V

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb finish	White (WH)

Approval and Application	
Energy efficiency label (EEL)	A+
Suitable for accent lighting	Yes
Energy Consumption kWh/1000 h	5 kWh


Product Data	
Full product code	871869648600900
Order product name	CorePro LEDspotMV 5-50W GU10 830 36D RN

CorePro LEDspot MV

EAN/UPC – product	8718696486009
Order code	48600900
Numerator – quantity per pack	1
Numerator – packs per outer box	10

Material no. (12NC)	929001156902
Net weight (piece)	0.038 kg

Dimensional drawing



LED 5-50W GU10 830 36D

Product	D	C
CorePro LEDspotMV 5-50W GU10 830 36D RN	50 mm	55 mm

Photometric data

