



Standard LED bulbs

Standard LEDBulb 9W E27 6500K W A19 1PF/6 MX

Standard LED bulbs are compatible with existing fixtures with a E27 holder and are designed for retrofit replacement of incandescent, halogen and energy saving bulbs. They deliver huge energy savings and minimize maintenance costs. The Standard LED bulb is the perfect bulb for your basic lighting needs. It provides the beautiful light and performance you expect from the LED technology at an affordable price.

Product data


General Information		Power Consumption	
Cap-Base	E27 [E27]	9 W	
Nominal lifetime	25,000 hour(s)	Wattage Equivalent	
Switching Cycle	50,000	60 W	
Lighting Technology	LED	Starting Time (Nom)	
EU RoHS compliant	Yes	0.5 s	
		Warm-up time to 60% light	
		0.5 s	
		Power Factor (Fraction)	
		0.92	
		Voltage (Nom)	
		100-240 V	
Light Technical		Temperature	
Color Code	865 [CCT of 6500K]	T-Case Maximum (Nom)	
Beam Angle (Nom)	150 degree(s)	80 °C	
Luminous Flux	806 lm		
Color Designation	Cool Daylight	Controls and Dimming	
Correlated Color Temperature (Nom)	6500 K	Dimmable	
Luminous Efficacy (rated) (Nom)	89.56 lm/W	No	
Color Consistency	ANSI		
Color rendering index (CRI)	80	Mechanical and Housing	
LLMF At End Of Nominal Lifetime (Nom)	70 %	Bulb Finish	
		Frosted	
		Bulb Shape	
		A19 [A 19mm]	
Operating and Electrical		Product Data	
Line Frequency	50 to 60 Hz	Order product name	
Input Frequency	50 to 60 Hz	LEDBulb 9W E27 6500K W A19 1PF/6 MX	
		Full product name	
		Standard LEDBulb 9W E27 6500K W A19 1PF/6 MX	

Standard LED bulbs

Order code	929001195441
Material Nr. (12NC)	929001195441
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677462918


Numerator - Packs per outer box	6
EAN/UPC - Case	50046677462913

Dimensional drawing




Product	D	C
LEDBulb 9W E27 6500K W A19 1PF/6 MX	60 mm	110 mm

Photometric data



Light Distribution Diagram - LEDBulb 9W E27 6500K W A19 1PF/6 MX



Spectral Power Distribution Colour - LEDBulb 9W E27 6500K W A19 1PF/6 MX

