



Standard LED bulbs

LEDBulb 9W E27 6500K W A19 2PF/6 MX

Standard LED bulbs are compatible with existing fixtures with a E27 holder and are designed for retrofit replacement of incandescent, halogen and energy saving bulbs. They deliver huge energy savings and minimize maintenance costs. The Standard LED bulb is the perfect bulb for your basic lighting needs. It provides the beautiful light and performance you expect from the LED technology at an affordable price.


Product data

General Information		Starting Time (Nom)		0.5 s
Cap-Base	E27 [E27]	Warm-up time to 60% light		0.5 s
Nominal lifetime	25,000 hour(s)	Power Factor (Fraction)		0.92
Switching Cycle	50,000	Voltage (Nom)		100-240 V
Lighting Technology	LED	Temperature		
EU RoHS compliant	Yes	T-Case Maximum (Nom)		80 °C
Light Technical		Controls and Dimming		
Color Code	865 [CCT of 6500K]	Dimmable		No
Beam Angle (Nom)	150 degree(s)	Mechanical and Housing		
Luminous Flux	806 lm	Bulb Finish		Frosted
Color Designation	Cool Daylight	Bulb Shape		A19 [A 19mm]
Correlated Color Temperature (Nom)	6500 K	Product Data		
Luminous Efficacy (rated) (Nom)	89.00 lm/W	Order product name		LEDBulb 9W E27 6500K W A19 2PF/6 MX
Color Consistency	ANSI	Full product name		LEDBulb 9W E27 6500K W A19 2PF/6 MX
Color rendering index (CRI)	80	Full product code		871869679300800
LLMF At End Of Nominal Lifetime (Nom)	70 %	Order code		929001195492
Operating and Electrical		Material Nr. (12NC)		929001195492
Line Frequency	50 to 60 Hz	Numerator - Quantity Per Pack		1
Input Frequency	50 to 60 Hz			
Power Consumption	9 W			

Standard LED bulbs


EAN/UPC - Product/Case	8718696793008
Numerator - Packs per outer box	6
EAN/UPC - Case	8718696793015

Dimensional drawing




Product	D	C
LEDBulb 9W E27 6500K W A19 2PF/6 MX	60 mm	110 mm

Photometric data



Light Distribution Diagram - LEDBulb 9W E27 6500K W A19 2PF/6 MX



Spectral Power Distribution Colour - LEDBulb 9W E27 6500K W A19 2PF/6 MX

