



# CorePro LED PLC 2P

## CorePro LED PLC 8.5W 830 2P G24d-3

CorePro LED PLC 2P integrates a LED light source into a traditional fluorescent form factor. This product is the ideal solution for uplamping in general lighting applications: it meets basic lighting requirements, offers significant energy savings, and is environmentally friendly.

### Product data

General Information	
Cap-Base	G24d-3
Nominal lifetime	30,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
CE mark	Yes
EU RoHS compliant	Yes

Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	120 degree(s)
Luminous Flux	950 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	105.88 lm/W
Color Consistency	<6
Color rendering index (CRI)	83
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RGO

Operating and Electrical	
Line Frequency	50 to 60 Hz

Input Frequency	50 to 60 Hz
Power Consumption	8.5 W
Lamp Current (Max)	43 mA
Lamp Current (Min)	33 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
LED alternative to fluorescent lamp power	26 W
Inrush current at mains	3.7
Max. lamp no. on MCB B type 10A - Mains	74
Max. lamp no. on MCB B type 10A – EM ballast without Comp. Cap.	150
Max. lamp no. on MCB B type 10A – EM ballast with Comp. Cap.	30
Max. lamp no. on MCB B type 16A - Mains	118
Max. lamp no. on MCB B type 16A – EM ballast without Comp. Cap.	220
Max. lamp no. on MCB B type 16A – EM ballast with Comp. Cap.	49
Ballast Compatibility	EM

# CorePro LED PLC 2P

## Temperature

Ambient temperature range	-20 °C to 35 °C
T-Case Maximum (Nom)	75 °C

## Controls and Dimming

Dimmable	No
----------	----

## Mechanical and Housing

Bulb Material	Plastic
Product Length	200 mm
Bulb Shape	PL-C

## Approval and Application


Energy Efficiency Class	F
Energy Saving Product	Yes
Approval Marks	TUV CE marking RoHS compliance KEMA Keur certificate

Energy Consumption kWh/1000 h	9 kWh
EPREL Registration Number	403554

## Product Data



Order product name	CorePro LED PLC 8.5W 830 2P G24d-3
Full product name	CorePro LED PLC 8.5W 830 2P G24d-3
Full product code	871869654123400
Order code	54123400
Material Nr. (12NC)	929001201202
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696541234
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696541241

## Dimensional drawing



Product	D1	D2	A1	A2	A3
CorePro LED PLC 8.5W 830 2P G24d-3	24.3 mm	28.4 mm	128.8 mm	148 mm	170.6 mm

## Photometric data



General uniform lighting - CorePro LED PLC 8.5W 830 2P G24d-3

Light Distribution Diagram - CorePro LED PLC 8.5W 830 2P G24d-3


# CorePro LED PLC 2P

## Photometric data




Spectral Power Distribution Colour - CorePro LED PLC 8.5W 830 2P G24d-3


## Lifetime




Life Expectancy Diagram - CorePro LED PLC 8.5W 830 2P G24d-3



Life Expectancy Diagram - CorePro LED PLC 8.5W 830 2P G24d-3




Life Expectancy Diagram - CorePro LED PLC 8.5W 830 2P G24d-3



Lumen Maintenance Diagram - CorePro LED PLC 8.5W 830 2P G24d-3

# CorePro LED PLC 2P

## Lifetime



Lumen Maintenance Diagram - CorePro LED PLC 8.5W 830 2P G24d-3

