



CorePro Plastic LEDcandles & lusters

CorePro candle ND 5.5-40W E14 840 B35 FR

The frosted CorePro LEDcandle is designed for retrofit replacement of incandescent lamps. It is compatible with fixtures with an E14 holder and is an attractive product for chandeliers. LEDlamps deliver huge energy savings and minimize maintenance cost.

Product data

General Information	
Cap-Base	E14 [E14]
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	840 [CCT of 4000K]
Luminous Flux	520 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	94.55 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz

Power Consumption	5.5 W
Lamp Current (Nom)	50 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.5
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	85 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	B35 [B 35mm]


Datasheet, 2023, April 29 data subject to change

CorePro Plastic LEDcandles & lusters

Approval and Application	
Energy Consumption kWh/1000 h	6 kWh
Product Data	
Order product name	CorePro candle ND 5.5-40W E14 840 B35 FR
Full product name	CorePro candle ND 5.5-40W E14 840 B35 FR
Full product code	871869654356600
Order code	929001205802


Material Nr. (12NC)	929001205802
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696543566
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696543573

Dimensional drawing




Product	D	С
CorePro candle ND 5.5-40W E14 840 B35 FR	35 mm	106 mm

Photometric data








Light Distribution Diagram - CorePro candle ND 5.5-40W E14 840 B35 FR




Spectral Power Distribution Colour - CorePro candle ND 5.5-40W E14 840 B35 FR

CorePro Plastic LEDcandles & lusters

Lifetime





Life Expectancy Diagram - CorePro candle ND 5.5-40W E14 840 B35 FR

Lumen Maintenance Diagram - CorePro candle ND 5.5-40W E14 840 B35 FR



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.