



LED BR30

BC9.5BR30/AMB/927/DIM 120V

Philips BR30 LED lamps are the smart alternative to standard incandescent. The traditional lamp design can provide excellent dimming performance with spectacular energy savings. They provide the beautiful light and dependable performance you expect from LED at an economical price.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	927
Beam Angle (Nom)	110 degree(s)
Luminous Flux	650 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	84.21 lm/W
Color Consistency	<6
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	60 Hz
Input Frequency	60 Hz
Power Consumption	9.5 W
Lamp Current (Nom)	100 mA

Wattage Equivalent	65 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	76 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	BR30
Approval and Application	
Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	- kWh
Product Data	
Order product name	BC9.5BR30/AMB/927/DIM 120V
Full product name	BC9.5BR30/AMB/927/DIM 120V


LED BR30

Order code	929001221803
Material Nr. (12NC)	929001221803
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677465209


Numerator - Packs per outer box	4
EAN/UPC - Case	50046677465204

Dimensional drawing


Product	D	C
BC9.5BR30/AMB/927/DIM 120V	96 mm	132 mm




Photometric data



Spectral Power Distribution Colour - BC9.5BR30/AMB/927/DIM 120V



General uniform lighting - BC9.5BR30/AMB/927/DIM 120V



Light Distribution Diagram - BC9.5BR30/AMB/927/DIM 120V

LED BR30

