PHILIPS Lighting

MASTER LEDtube EM/ Mains T8

MAS LEDtube 1200mm 16W830 T8 I

The Philips MASTER LEDtube integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance, which cannot be distinguished from traditional fluorescent. These T8 LED tubes are the right choice for absolute performance and are designed to stand up to everyday conditions. Unparalleled savings thanks to low energy consumption and an exceptionally long lifetime ensure this tube masters every demanding application.

Warnings and Safety

• NOTE: The overall energy efficiency and light distribution of any installation that uses these lamps will be determined by the design of the installation.

Product data

| General Information | | LLMF At End Of Nominal Lifetime (Nom) 70 % | |
|------------------------------------|---------------------------------|--|-------------|
| Cap-Base | G13 [Medium Bi-Pin Fluorescent] | | |
| Nominal lifetime | 50,000 hour(s) | Operating and Electrical | |
| Switching Cycle | 20,000 | Line Frequency | 50 to 60 Hz |
| Lighting Technology | LED | Input Frequency | 50 to 60 Hz |
| EU RoHS compliant | Yes | Power Consumption | 16 W |
| | | Lamp Current (Max) | 77 mA |
| Light Technical | | Lamp Current (Min) | 68 mA |
| Color Code | 830 [CCT of 3000K] | Starting Time (Nom) | 0.5 s |
| Luminous Flux | 2,000 lm | Warm-up time to 60% light | 0.5 s |
| Correlated Color Temperature (Nom) | 3000 K | Power Factor (Fraction) | 0.9 |
| Color Consistency | <6 | Voltage (Nom) | 220-240 V |
| Color rendering index (CRI) | 80 | | |
| | | | |

MASTER LEDtube EM/Mains T8

| Temperature | | |
|------------------------------|--------------------------------------|--|
| Ambient temperature range | -20 ℃ to 35 ℃ | |
| T-Case Maximum (Nom) | 55 ℃ | |
| | | |
| Controls and Dimming | | |
| Dimmable | No | |
| | | |
| Mechanical and Housing | | |
| Product Length | 1,200 mm | |
| | | |
| Approval and Application | | |
| Energy Saving Product | Yes | |
| Suitable For Accent Lighting | No | |
| Approval Marks | CE marking RoHS compliance KEMA Keur | |
| | certificate | |
| | | |

| Energy Consumption kWh/1000 h | 16 kWh | |
|---------------------------------|--------------------------------|--|
| | | |
| Product Data | | |
| Order product name | MAS LEDtube 1200mm 16W830 T8 I | |
| Full product name | MAS LEDtube 1200mm 16W830 T8 I | |
| Full product code | 871869667636300 | |
| Order code | 929001249008 | |
| Material Nr. (12NC) | 929001249008 | |
| Numerator - Quantity Per Pack | 1 | |
| EAN/UPC - Product/Case | 8718696676363 | |
| Numerator - Packs per outer box | 10 | |
| EAN/UPC - Case | 8718696676370 | |
| | | |

Dimensional drawing



Photometric data



Spectral Power Distribution Colour - MAS LEDtube 1200mm 16W830 T8 I

General uniform lighting - MAS LEDtube 1200mm 16W830 T8 I

MASTER LEDtube EM/Mains T8

Photometric data



Light Distribution Diagram - MAS LEDtube 1200mm 16W830 T8 I



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, October 26 - data subject to change