PHILIPS

Lighting



Essential LEDspot MR16

ESS LED MR16 4.5-50W 36D 830 100-240V

Essential LEDspots MR16 are compatible with most existing fixtures with a GU5.3 socket and are designed as a retrofit replacement for halogen spots. Essential LEDspots MR16 deliver significant energy savings and minimize initial investment.

Product data

General Information	
Cap-Base	GU5.3 [GU5.3]
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	36 degree(s)
Luminous Flux	400 lm
Luminous Intensity (Nom)	750 cd
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	88.89 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	4.5 W
Lamp Current (Nom)	80 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	1 s
Power Factor (Fraction)	0.4
Voltage (Nom)	100-240 V

Temperature	
T-Case Maximum (Nom)	90 °C

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Shape	MR16 [2inch/50mm]

Approval and Application	
Suitable For Accent Lighting	Yes

Essential LEDspot MR16


Energy Consumption kWh/1000 h	5 kWh

Material Nr. (12NC)	929001274408
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696685709
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696685716

Product Data


Order product name	ESS LED MR16 4.5-50W 36D 830 100-240V
Full product name	ESS LED MR16 4.5-50W 36D 830 100-240V
Full product code	871869668570900
Order code	929001274408

Dimensional drawing




Product	D	C
ESS LED MR16 4.5-50W 36D 830 100-240V	51 mm	49 mm


Photometric data



Spectral Power Distribution Colour - ESS LED MR16 4.5-50W 36D 830 100-240V




General uniform lighting - ESS LED MR16 4.5-50W 36D 830 100-240V




Light Distribution Diagram - ESS LED MR16 4.5-50W 36D 830 100-240V

Essential LEDspot MR16

Lifetime



Life Expectancy Diagram - ESS LED MR16 4.5-50W 36D 830 100-240V



Lumen Maintenance Diagram - ESS LED MR16 4.5-50W 36D 830 100-240V

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.