



# MASTER LEDtube InstantFit HF T5

## MAS LEDtube HF 1500mm HO 26W 840 T5

Philips MASTER LEDtube InstantFit T5 integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance which cannot be distinguished from traditional fluorescent. The Philips MASTER LEDtube InstantFit T5 is the ideal solution for customers who have higher light output requirements and want to maximize value over lifetime. Full energy savings & longer lifetime result in attractive payback times and TCO benefits.

### Product data

General Information		Lamp Current (Min)		
Cap-Base	G5 [ G5]	240 mA		
Nominal Lifetime (Nom)	50000 h	Starting Time (Nom)		0.5 s
Switching Cycle	50000X	Warm Up Time to 60% Light (Nom)		0.5 s
B50L70	50000 h	Power Factor (Nom)		0.9
Voltage (Nom)		100-135 V		
Light Technical		Temperature		
Color Code	840 [ CCT of 4000K]	T-Ambient (Max)		45 °C
Luminous Flux (Nom)	3900 lm	T-Ambient (Min)		-20 °C
Luminous Flux (Rated) (Nom)	3900 lm	T-Storage (Max)		65 °C
Correlated Color Temperature (Nom)	4000 K	T-Storage (Min)		-40 °C
Color Consistency	<6	T-Case Maximum (Nom)		45 °C
Color Rendering Index (Nom)	83	Controls and Dimming		
LLMF At End Of Nominal Lifetime (Nom)	70 %	Dimmable		No
Operating and Electrical		Mechanical and Housing		
Input Frequency	39000-60000 Hz	Product Length		1500 mm
Power (Rated) (Nom)	26 W			
Lamp Current (Max)	415 mA			



# MASTER LEDtube InstantFit HF T5

## Lifetime

