



Essential LED bulbs

ESS LEDBulb 14W E27 6500K HV 1PF/20 AR

Essential LEDbulbs are compatible with existing fixtures with a E27 holder and are designed for retrofit replacement of incandescent, halogen and energy saving bulbs. They deliver huge energy savings and minimize initial investment

Product data

General Information	
Cap-Base	E27 [E27]
Nominal lifetime	10,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	765 [CCT of 6500K]
Beam Angle (Nom)	150 degree(s)
Luminous Flux	1,521 lm
Color Designation	Cool Daylight
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	108.00 lm/W
Color Consistency	<7
Color rendering index (CRI)	70
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	14 W
Lamp Current (Nom)	120 mA
Wattage Equivalent	120 W

Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.5
Voltage (Nom)	220-240 V

Temperature	
T-Case Maximum (Nom)	85 °C

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	A60 [A 60mm]

Approval and Application	
Energy Consumption kWh/1000 h	- kWh

Product Data	
Order product name	ESS LEDBulb 14W E27 6500K HV 1PF/20 AR
Full product name	ESS LEDBulb 14W E27 6500K HV 1PF/20 AR
Full product code	871869960543800
Order code	929001312571
Material Nr. (12NC)	929001312571

Essential LED bulbs



Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699605438
Numerator - Packs per outer box	20

EAN/UPC - Case	8718699605445
----------------	---------------

Dimensional drawing

Product	D	C
ESS LEDBulb 14W E27 6500K HV 1PF/20 AR	60 mm	110 mm

Photometric data




General uniform lighting - ESS LEDBulb 14W E27 6500K HV 1PF/20 AR

Spectral Power Distribution Colour - ESS LEDBulb 14W E27 6500K HV 1PF/20 AR

Light Distribution Diagram - ESS LEDBulb 14W E27 6500K HV 1PF/20 AR

Essential LED bulbs

Lifetime



Life Expectancy Diagram - ESS LEDBulb 14W E27 6500K HV 1PF/20 AR

Lumen Maintenance Diagram - ESS LEDBulb 14W E27 6500K HV 1PF/20 AR

