



FG

MASTER LEDspot ExpertColor MV

MAS LED ExpertColor 5.5-50W GU10 940 36D

MASTER LEDspot ExpertColor creates a warm and comfortable ambience for hospitality venues, homes and restaurants. They offer superior lighting that has a customized spectrum, high CRI, and deep dimming feature. What's more the innovative, trimless lens design will also suit almost any interior decor with its clean and neat look. In addition, with MASTER LEDspot ExpertColor you can take advantage of the full ExpertColor family, which also includes LEDspot MR16, LEDspot AR111 and LEDspot PAR lamps. MASTER LEDspot ExpertColor delivers huge energy savings and minimizes maintenance costs without any compromise on light quality and lifetime, enabling residential and business owners to achieve a return on their investment within a short time period.

Product data

General Information		
Cap-Base	GU10	
Nominal lifetime	40,000 hour(s)	
Switching Cycle	50,000	
Lighting Technology	LED	
Flux measurement reference	Narrow Cone	
CE mark	Yes	
EU RoHS compliant	Yes	
Light Technical		
Color Code	940 [CCT of 4000K]	
Beam Angle (Nom)	36 degree(s)	
Luminous Flux	400 lm	
Luminous Intensity (Nom)	800 cd	
Color Designation	Cool White (CW)	

Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	72.00 lm/W
Color Consistency	<3
Color rendering index (CRI)	97
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	400 lm
Flickering value (PstLM) - Flickering value as	1
per EN 61000-3-3	
Stroboscopic effect visibility measure (SVM)	0.4
Photobiological safety according to EN 62471	RG1
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	5.5 W


Datasheet, 2024, March 14 data subject to change

MASTER LEDspot ExpertColor MV

Lamp Current (Nom)	30 mA	
Wattage Equivalent	50 W	
Starting Time (Nom)	0.5 s 0.5 s	
Warm-up time to 60% light		
Power Factor (Fraction)	0.8	
Voltage (Nom)	220-240 V	
Temperature		
T-Case Maximum (Nom)	80 °C	
Controls and Dimming		
Dimmable	Only with specific dimmers	
Mechanical and Housing		
Bulb Shape	PAR16	
Approval and Application		
Energy Efficiency Class	F	
Suitable For Accent Lighting	Yes	
Energy Consumption kWh/1000 h	6 kWh	


EPREL Registration Number	391835
EyeComfort	Yes
Application Conditions	
can it be used in closed luminaires	No
Product Data	
Order product name	MAS LED ExpertColor 5.5-50W GU10
	940 36D
Full product name	MAS LED ExpertColor 5.5-50W GU10
	940 36D
Full product code	871869670771500
Order code	929001347502
Material Nr. (12NC)	929001347502
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696707715
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696707722

Dimensional drawing




Product	D	С
MAS LED ExpertColor 5.5-50W GU10 940 36D	50 mm	54 mm

Photometric data




Accent Lighting Spots - MAS LED ExpertColor 5.5-50W GU10 940 36D



Spectral Power Distribution Colour - MAS LED ExpertColor 5.5-50W GU10 940 36D


MASTER LEDspot ExpertColor MV


Photometric data



Light Distribution Diagram - MAS LED ExpertColor 5.5-50W GU10 940 36D

Lifetime





Life Expectancy Diagram - MAS LED ExpertColor 5.5-50W GU10 940 36D

Lumen Maintenance Diagram - MAS LED ExpertColor 5.5-50W GU10 940 36D



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.