



MASTER VALUE LEDspot MV



MAS LED spot VLE D 3.7-35W GU10 940 36D

Delivering a warm, halogen-like accent beam, MASTER VALUE is a perfect fit for spot lighting. Thanks to its high CRI, it realizes more natural colors, creating cozy and comfortable ambiances for residential and hospitality projects, and emphasizing the beauty of merchandise in retail. These LED spots MV GU10 have the familiar look and feel of spot lamps, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables you to create the atmosphere you desire, and it works with broad selection of dimmers. MASTER VALUE also offers more energy savings that normal LED spots.

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

Product data

General Information	
Cap-Base	GU10
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Narrow Cone
CE mark	Yes
EU RoHS compliant	Yes
Light Technical	
Color Code	940 [CCT of 4000K]

Beam Angle (Nom)	36 degree(s)
Luminous Flux	285 lm
Luminous Intensity (Nom)	500 cd
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	85.14 lm/W
Color Consistency	<6
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	285 lm

MASTER VALUE LEDspot MV

Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Photobiological safety according to EN 62471	RG1

Operating and Electrical

Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	3.7 W
Lamp Current (Nom)	20 mA
Wattage Equivalent	35 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.8
Voltage (Nom)	220-240 V

Temperature

T-Case Maximum (Nom)	80 °C
----------------------	-------

Controls and Dimming

Dimmable	Only with specific dimmers
----------	----------------------------

Mechanical and Housing

Bulb Shape	PAR16
------------	-------

Approval and Application

Energy Efficiency Class	F
Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	4 kWh
EPREL Registration Number	391885
EyeComfort	Yes


Application Conditions

can it be used in closed luminaires	No
-------------------------------------	----

Product Data

Order product name	MAS LED spot VLE D 3.7-35W GU10 940 36D
Full product name	MAS LED spot VLE D 3.7-35W GU10 940 36D
Full product code	871869670777700
Order code	929001348402
Material Nr. (12NC)	929001348402
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696707777
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696707784


Dimensional drawing



Product	D	C
MAS LED spot VLE D 3.7-35W GU10 940 36D	50 mm	54 mm



Lifetime



An empty line graph with the y-axis labeled 'Richtig in %' (Correct in %) ranging from 80 to 100 in increments of 10. The x-axis represents the number of questions, with 6 grid lines corresponding to questions 1 through 6. A line is drawn from (1, 100) to (6, 80).

Datasheet, 2024, March 14

MASTER VALUE LEDspot MV

