



MASTER VALUE LEDspot MV

MAS LED spot VLE D 650lm GU10 830 120D

Delivering a warm, halogen-like accent beam, MASTER VALUE is a perfect fit for spot lighting. Thanks to its high CRI, it realizes more natural colors, creating cozy and comfortable ambiences for residential and hospitality projects, and emphasizing the beauty of merchandise in retail. These LED spots MV GU10 have the familiar look and feel of spot lamps, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables you to create the atmosphere you desire, and it works with broad selection of dimmers. MASTER VALUE also offers more energy savings that normal LED spots.

Warnings and Safety

- · Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

Product data

General Information	
Cap-Base	GU10 [GU10]
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	120 degree(s)
Luminous Flux	650 lm

Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	92.86 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz

Datasheet, 2023, November 12 data subject to change


Power Consumption

MASTER VALUE LEDspot MV

Lamp Current (Nom)	35 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.8
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	85 ℃
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Shape	PAR16 [PAR 2 inch/50mm]


7 kWh
MAS LED spot VLE D 650lm GU10 830 120D
MAS LED spot VLE D 650lm GU10 830 120D
871869672431600
929001349702
929001349702
1
8718696724316
10
8718696724323

Dimensional drawing




Product	D	С
MAS LED spot VLE D 650lm GU10 830 120D	50 mm	54 mm

Photometric data






Accent Lighting Spots - MAS LED spot VLE D 650lm GU10 830 120D



Light Distribution Diagram - MAS LED spot VLE D 650lm GU10 830 120D


MASTER VALUE LEDspot MV


Photometric data



Spectral Power Distribution Colour - MAS LED spot VLE D 650lm GU10 830 120D

Lifetime





Life Expectancy Diagram - MAS LED spot VLE D 650lm GU10 830 120D

Lumen Maintenance Diagram - MAS LED spot VLE D 650lm GU10 830 120D



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.