



# TrueForce LED Industrial and Retail (Highbay – HPI/SON/HPL)

## TrueForce LED HPI ND 200-145W E40 840 120D

Philips TrueForce LED Industrial and Retail lamps give you a quick and easy payback solution to replace HID lamps in Highbay application. The solution gives you the LED benefits of energy-efficiency and long-lifetime, plus they come for a low initial investment. With unique lamp design and compatibility, you can directly retrofit HID lamps with TrueForce LED lamps without changing the fixtures or gear. Multiple beam angle options and high colour rendering index enhance the lighting distribution while creating a comfortable, safe and high productivity environment.

#### **Warnings and Safety**

• EM version requires an EM ballast to operate. Please refer to the installation guide or consult a Philips Lighting representative.

#### **Product data**

General Information	
Cap-Base	E40 [E40]
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	120 degree(s)

Luminous Flux	20,000 lm	
Color Designation	Cool White (CW)	
Correlated Color Temperature (Nom)	4000 K	
Luminous Efficacy (rated) (Nom)	137.00 lm/W	
Color Consistency	<6	
Color rendering index (CRI)	80	
LLMF At End Of Nominal Lifetime (Nom) 70 %		
Operating and Electrical		
Line Frequency	50 Hz	


Datasheet, 2023, April 29 data subject to change

# TrueForce LED Industrial and Retail (Highbay - HPI/SON/HPL)

Input Frequency	50 Hz
Power Consumption	145 W
Lamp Current (Nom)	3,900 mA
Starting Time (Nom)	0.7 s
Warm-up time to 60% light	0.7 s
Power Factor (Fraction)	0.7
Voltage (Nom)	100-145 V
Temperature	
T-Case Maximum (Nom)	95 ℃
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Shape	Others


160 kWh
TForce LED HPI ND 200-145W E40 840 120D
TrueForce LED HPI ND 200-145W E40 840
120D
871869671388400
71388400
929001357102
1
8718696713884
2
8718696713891

## Dimensional drawing




Product	D	С
TForce LED HPI ND 200-145W E40 840 120D	210 mm	250 mm

## Photometric data








Light Distribution Diagram - TForce LED HPI ND 200-145W E40 840 120D


# TrueForce LED Industrial and Retail (Highbay - HPI/SON/HPL)


### Photometric data



Spectral Power Distribution Colour - TForce LED HPI ND 200-145W E40 840 120D


### Lifetime





Life Expectancy Diagram - TForce LED HPI ND 200-145W E40 840 120D

Lumen Maintenance Diagram - TForce LED HPI ND 200-145W E40 840 120D



Life Expectancy Diagram - TForce LED HPI ND 200-145W E40 840 120D

# TrueForce LED Industrial and Retail (Highbay - HPI/SON/HPL)



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.