

LED Urban TrueForce Lamps

26ED23.5/LED/727/ND 120-277V G2 4/1

Philips TrueForce LED high lumen post top lamp makes it easy to upgrade to long lasting, energy saving LED technology without sacrificing your site's unique outdoor character. Philips TrueForce is a direct replacement option which ensures a perfect fit with existing modern and traditional luminaires. We claim true replacement when comparing flux. This post top lamps can be used in enclosed fixtures.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	727 [CCT of 2700K]
Beam Angle (Nom)	360 degree(s)
Luminous Flux	2,800 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	107.00 lm/W
Color Consistency	ANSI 2700K
Color rendering index (CRI)	70
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	26 W
Lamp Current (Nom)	220 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	120-277 V

Temperature	
T-Case Maximum (Nom)	60 °C

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Plastic
Bulb Shape	Others


LED Urban TrueForce Lamps

Approval and Application	
Energy Consumption kWh/1000 h	- kWh

Product Data	
Order product name	26ED23.5/LED/727/ND 120-277V G2 4/1
Full product name	26ED23.5/LED/727/ND 120-277V G2 4/1
Order code	473595


Material Nr. (12NC)	929001396404
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677473594
Numerator - Packs per outer box	4
EAN/UPC - Case	50046677473599

Dimensional drawing




Product	D	C
26ED23.5/LED/727/ND 120-277V G2 4/1	84 mm	176 mm


Photometric data



General uniform lighting - 26ED23.5/LED/727/ND 120-277V G2 4/1




Light Distribution Diagram - 26ED23.5/LED/727/ND 120-277V G2 4/1




Spectral Power Distribution Colour - 26ED23.5/LED/727/ND 120-277V G2 4/1

LED Urban TrueForce Lamps

Lifetime



Life Expectancy Diagram - 26ED23.5/LED/727/ND 120-277V G2 4/1



Lumen Maintenance Diagram - 26ED23.5/LED/727/ND 120-277V G2 4/1

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.