



# A-Shape LED

## 16A21/PER/850/P/E26/DIM 6/1FB

Philips A-shape LED lamps are the LED alternative to standard incandescents. It provides beautiful light and dependable performance you expect from LED at an affordable price.


### Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	850 [CCT of 5000K]
Beam Angle (Nom)	250 degree(s)
Luminous Flux	1,600 lm
Color Designation	Daylight
Correlated Color Temperature (Nom)	5000 K
Luminous Efficacy (rated) (Nom)	100.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	60 Hz
Input Frequency	60 Hz
Power Consumption	16 W
Lamp Current (Nom)	180 mA
Wattage Equivalent	100 W

Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.8
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	90 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	A21 [A 21mm]
Product Data	
Order product name	16A21/PER/850/P/E26/DIM 6/1FB
Full product name	16A21/PER/850/P/E26/DIM 6/1FB
Order code	929001837004
Material Nr. (12NC)	929001837004
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677479497
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677479492



A-Shape LED

Dimensional drawing



Product	D	C
16A21/PER/850/P/E26/DIM 6/1FB	78 mm	140 mm


Photometric data



General Uniform Lighting

Light Distribution Diagram - 16A21/PER/850/P/E26/DIM 6/1FB


General uniform lighting - 16A21/PER/850/P/E26/DIM 6/1FB




Spectral Power Distribution Colour - 16A21/PER/850/P/E26/DIM 6/1FB

A-Shape LED

Lifetime



Lumen Maintenance Diagram - 16A21/PER/850/P/E26/DIM 6/1FB



Life Expectancy Diagram - 16A21/PER/850/P/E26/DIM 6/1FB

