

A-Shape LED

6A19/PER/850/CL/G/DIM 6/1CT

Philips A-shape LED lamps are the LED alternative to standard incandescents. It provides beautiful light and dependable performance you expect from LED at an affordable price.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	850 [CCT of 5000K]
Luminous Flux	450 lm
Color Designation	Daylight
Correlated Color Temperature (Nom)	5000 K
Luminous Efficacy (rated) (Nom)	75.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	6 W
Lamp Current (Nom)	47 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s

Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.7
Voltage (Nom)	120 V

Temperature	
T-Case Maximum (Nom)	95 °F


Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	A19 [A 19mm]

Product Data	
Order product name	6A19/PER/850/CL/G/DIM 6/1CT
Full product name	6A19/PER/850/CL/G/DIM 6/1CT
Order code	478636
Material Nr. (12NC)	929001840104
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677478636
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677478631



A-Shape LED

Dimensional drawing




Product	D	C
6A19/PER/850/CL/G/DIM 6/1CT	60 mm	103 mm

Photometric data



General uniform lighting - 6A19/PER/850/CL/G/DIM 6/1CT


Spectral Power Distribution Colour - 6A19/PER/850/CL/G/DIM 6/1CT




Light Distribution Diagram - 6A19/PER/850/CL/G/DIM 6/1CT

A-Shape LED

Lifetime



Lumen Maintenance Diagram - 6A19/PER/850/CL/G/DIM 6/1CT



Life Expectancy Diagram - 6A19/PER/850/CL/G/DIM 6/1CT

