PHILIPS

Lighting



LED Highbay

125HB/LED/750/ND WB DL BB 2/1

Philips LED high bay lamps are a direct replacement for 250W to 400W metal halide lamps which will deliver substantial energy savings. Philips LED HighBays delivers bright, clean light for a fraction of the energy used by conventional HID.

Product data

General Information	
Cap-Base	EX39 [Exclusionary Mogul Screw]
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	750 [CCT of 5000K]
Beam Angle (Nom)	130 degree(s)
Luminous Flux	16,000 lm
Color Designation	Daylight
Correlated Color Temperature (Nom)	5000 K
Luminous Efficacy (rated) (Nom)	128.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	70
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	125 W
Lamp Current (Nom)	1,100 mA
Wattage Equivalent	320 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	120-277 V
UL Type	Type B - bypass the ballast

Temperature	
T-Case Maximum (Nom)	75 °C

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Shape	Others

Approval and Application	
Energy Consumption kWh/1000 h	- kWh
Energy Certifications	DLC Standard


Product Data	
Order product name	125HB/LED/750/ND WB DL BB 2/1
Full product name	125HB/LED/750/ND WB DL BB 2/1
Order code	478123
Material Nr. (12NC)	929001852604

LED Highbay

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677478124
Numerator - Packs per outer box	2


EAN/UPC - Case	50046677478129

Dimensional drawing




Product	D	C
125HB/LED/750/ND WB DL BB 2/1	211 mm	252 mm


Photometric data



General uniform lighting - 125HB/LED/750/ND WB DL BB 2/1




Light Distribution Diagram - 125HB/LED/750/ND WB DL BB 2/1




Spectral Power Distribution Colour - 125HB/LED/750/ND WB DL BB 2/1

LED Highbay

Lifetime



Life Expectancy Diagram - 125HB/LED/750/ND WB DL BB 2/1



Lumen Maintenance Diagram - 125HB/LED/750/ND WB DL BB 2/1

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.