

LED PAR30 S/L

11.3PAR30S/PER/930/F40/DIM/120V 6/1FBT20

Philips LED spots with a single optic beam, provide a clean beam that's free from shadows with beam angles from 15 and 40 degrees to suit every general lighting application.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	40 degree(s)
Luminous Flux	850 lm
Luminous Intensity (Nom)	2,000 cd
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	75.00 lm/W
Color Consistency	<4
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	60 Hz
Input Frequency	60 Hz
Power Consumption	11.3 W
Lamp Current (Nom)	120 mA
Wattage Equivalent	75 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	120 V

Temperature	
T-Case Maximum (Nom)	90 °C

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Plastic
Bulb Shape	PAR30S [PAR 3.75 inch/95mm Short]

Approval and Application	
Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	- kWh


Product Data	
Order product name	11.3PAR30S/PER/930/F40/DIM/120V 6/1FBT20

LED PAR30 S/L

Full product name	11.3PAR30S/PER/930/F40/DIM/120V 6/1FBT20
Order code	929001854204
Material Nr. (12NC)	929001854204
Numerator - Quantity Per Pack	1


EAN/UPC - Product/Case	046677535407
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677535402

Dimensional drawing




Product	D	C
11.3PAR30S/PER/930/F40/DIM/120V 6/1FBT20	94.8 mm	93.1 mm


Photometric data



Light Distribution Diagram - 11.3PAR30S/PER/930/F40/DIM/120V 6/1FBT20




Accent Lighting Spots - 11.3PAR30S/PER/930/F40/DIM/120V 6/1FBT20




Spectral Power Distribution Colour - 11.3PAR30S/PER/930/F40/DIM/120V 6/1FBT20

LED PAR30 S/L

Lifetime



Life Expectancy Diagram - 11.3PAR30S/PER/930/F40/DIM/120V 6/1FBT20



Lumen Maintenance Diagram - 11.3PAR30S/PER/930/F40/DIM/120V 6/1FBT20

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.