



MASTER LEDspot LV

MASTER LED 6.5-50W 940 MR16 24D CN

Delivering intense accent beam, MASTER LEDspot LV is an ideal retrofit solution for spot lighting. MASTER LEDspot LV is designed to replace halogen or incandescent spots. It realizes natural colors, enables cozy and comfortable ambience for residential, hospitality and emphasizes the beauty of merchandise in retail. New smaller housing provides perfect fitting with majority of luminaires in a market with a MR16 GU 5.3 holder. It not only employs Philips' patented solution to guarantee the broadest possible compatibility with standard 12V halogen electronic transformers, it also delivers high beam intensity which is equivalent to halogen MR16 spots. The dimming function enables to create the desired atmosphere and it works with broad selection of dimmers. Its high SDCM ensure stricter color consistency, that is maintained over product life. MASTER LEDspot LV delivers huge energy savings and minimizes maintenance cost without any compromise on light quality and lifetime, enabling residential and business owners to achieve a return on their investment within short period time.

Product data

General Information	
Cap-Base	GU5.3
Nominal lifetime	40,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	940 [CCT of 4000K]
Beam Angle (Nom)	24 degree(s)
Luminous Flux	520 lm
Luminous Intensity (Nom)	2,500 cd
Color Designation	Cool White (CW)

Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	80.00 lm/W
Color Consistency	<4
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	- Hz
Input Frequency	- Hz
Power Consumption	6.5 W
Lamp Current (Nom)	720 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s


Datasheet, 2024, March 11 data subject to change

MASTER LEDspot LV

Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.7
Voltage (Nom)	12 V
Temperature	
T-Case Maximum (Nom)	90 ℃
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	MR16
Approval and Application	
Suitable For Accent Lighting	Yes


Energy Consumption kWh/1000 h	8 kWh
Product Data	
Order product name	MASTER LED 6.5-50W 940 MR16 24D CN
Full product name	MASTER LED 6.5-50W 940 MR16 24D CN
Full product code	692234190527800
Order code	929001882110
Material Nr. (12NC)	929001882110
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6922341905278
Numerator - Packs per outer box	10
EAN/UPC - Case	6922341905285


Dimensional drawing



Product	D	С
MASTER LED 6.5-50W 940 MR16 24D CN	50.5 mm	46.5 mm

Photometric data






Spectral Power Distribution Colour - MASTER LED 6.5-50W 940 MR16 24D CN $\,$

Light Distribution Diagram - MASTER LED 6.5-50W 940 MR16 24D CN

MASTER LEDspot LV


Photometric data



Calculus Photometrics 4.5 Philips Lighting ScV. Page: 17

Accent Lighting Spots - MASTER LED 6.5-50W 940 MR16 24D CN

Lifetime



Lumen Maintenance Diagram - MASTER LED 6.5-50W 940 MR16 24D CN

Life Expectancy Diagram - MASTER LED 6.5-50W 940 MR16 24D CN



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.