



LED PAR38

16.5PAR38/PER/927/F25/DIM/120V 6/1FB T20

Philips LED spots with a single optic beam, provide a clean beam that's free from shadows with beam angles from 15 and 40 degrees to suit every general lighting application.


Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	25000 h
Switching Cycle	50000X
Technical Type	16.5-120W
Light Technical	
Color Code	927
Beam Angle (Nom)	25 °
Luminous Flux (Nom)	1150 lm
Luminous Intensity (Nom)	5800 cd
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	69.00 lm/W
Color Consistency	<4
Color Rendering Index (Nom)	95
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	60 Hz
Power (Nom)	16.5 W
Lamp Current (Nom)	170 mA
Wattage Equivalent	120 W

Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.9
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	90 °C
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Energy Efficiency Label (EEL)	Not applicable
Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	- kWh
Product Data	
Order product name	16.5PAR38/PER/927/F25/DIM/120V 6/1FB T20
EAN/UPC - Product	046677534875
Order code	929001909104
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929001909104
Net Weight (Piece)	0.385 kg

LED PAR38


Dimensional drawing




PAR38 17-120W 1250lm 25D 2700K E26 ND

Product	D	C
16.5PAR38/PER/927/F25/DIM/120V 6/1FB T20	120.7 mm	134.6 mm


Photometric data



LEDspot PAR38 E26 927 25°





LEDspot PAR38 E26



LEDspot PAR38 E26 927 25°

LED PAR38

Lifetime



LEDspot E26

LEDspot E26

