

TrueForce High Lumen PAR

25.5PAR30L/PER/930/S15/ND/120-277V 6/1FB

Philips LED TrueForce PAR high lumen lamps are the perfect transition from CDM lamps to LED.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	15 degree(s)
Luminous Flux	2,150 lm
Luminous Intensity (Nom)	13,500 cd
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	84.00 lm/W
Color Consistency	<4
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	25.5 W
Wattage Equivalent	75 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.8
Voltage (Nom)	120-277 V

Temperature	
T-Case Maximum (Nom)	203 °F

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Aluminum
Bulb Shape	PAR30L [PAR 3.75 inch/95mm Long]


Approval and Application	
Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	- kWh

TrueForce High Lumen PAR

Product Data	
Order product name	25.5PAR30L/PER/930/S15/ND/120-277V 6/1FB
Full product name	25.5PAR30L/PER/930/S15/ND/120-277V 6/1FB
Order code	534669
Material Nr. (12NC)	929001917204


Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677534660
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677534665

Dimensional drawing




Product	D	C
25.5PAR30L/PER/930/S15/ND/120-277V 6/1FB	96 mm	119 mm


Photometric data



Light Distribution Diagram - 25.5PAR30L/PER/930/S15/ND/120-277V 6/1FB




Spectral Power Distribution Colour - 25.5PAR30L/PER/930/S15/ND/120-277V 6/1FB




Accent Lighting Spots - 25.5PAR30L/PER/930/S15/ND/120-277V 6/1FB

TrueForce High Lumen PAR

Lifetime



Life Expectancy Diagram - 25.5PAR30L/PER/930/S15/ND/120-277V 6/1FB



Lumen Maintenance Diagram - 25.5PAR30L/PER/930/S15/ND/120-277V 6/1FB

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.