



# TrueForce High Lumen PAR

33PAR38/PER/830/F25/DIM/120V B 6/1FB

Philips LED TrueForce PAR high lumen lamps are the perfect transition from CDM lamps to LED.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	25 degree(s)
Luminous Flux	3,000 lm
Luminous Intensity (Nom)	10,000 cd
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	90.00 lm/W
Color Consistency	<4
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz

Power Consumption	33 W
Lamp Current (Nom)	300 mA
Wattage Equivalent	250 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.95
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	90 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Aluminum
Bulb Shape	PAR38
UL Wet/ damp/ dry location	Damp location
Approval and Application	
Suitable For Accent Lighting	Yes

TrueForce High Lumen PAR

Energy Consumption kWh/1000 h	- kWh
Energy Certifications	Energy Star
T20 compliant	N/A

Application Conditions


can it be used in closed luminaires	No
-------------------------------------	----

Product Data

Order product name	33PAR38/PER/830/F25/DIM/120V B 6/1FB
--------------------	--------------------------------------



Full product name	33PAR38/PER/830/F25/DIM/120V B 6/1FB
Order code	929001919704
Material Nr. (12NC)	929001919704
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677534639
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677534634

Dimensional drawing



Product	D	C
33PAR38/PER/830/F25/DIM/120V B 6/1FB	123 mm	133 mm

Photometric data




Accent Lighting Spots - 33PAR38/PER/830/F25/DIM/120V B 6/1FB

Light Distribution Diagram - 33PAR38/PER/830/F25/DIM/120V B 6/1FB


TrueForce High Lumen PAR

Photometric data




Spectral Power Distribution Colour - 33PAR38/PER/830/F25/DIM/120V B 6/1FB

Lifetime



Life Expectancy Diagram - 33PAR38/PER/830/F25/DIM/120V B 6/1FB



Lumen Maintenance Diagram - 33PAR38/PER/830/F25/DIM/120V B 6/1FB

