



T8

14.5T8/MAS/48-830/MF20/P 10/1

Introducing Philips MainsFit (UL Type B) MasterClass T8 LED tubes with industry leading reliability, shatter-prevention and lifetime. The UL Type B LED tubes are designed with easy installation and long-term maintenance simplicity in mind. Upgrade your lighting to MasterClass and realize 70,000 hour LED lifetime backed by a 7-year, full replacement limited warranty.

Product data


General information		Lamp Current (Max)	
Base	G13 [Medium Bi-Pin Fluorescent]	Lamp Current (Max)	125 mA
EU RoHS compliant	Yes	Lamp Current (Min)	54 mA
Nominal Lifetime (Nom)	70000 h	Wattage Equivalent	32 W
Switching Cycle	50000X	Starting Time (Nom)	0.5 s
Technical Type	14.5-32W	Warm Up Time to 60% Light (Nom)	0.8 s
Light technical		UL Type	Type B - bypass the ballast
Color Code	830 [CCT of 3000K]	Power Factor (Nom)	0.9
Beam Angle (Nom)	180 °	Voltage (Nom)	120-277 V
Initial lumen (Nom)	2000 lm	Temperature	
Luminous Flux (Rated) (Nom)	2000 lm	T-Ambient (Max)	45 °C
Color Designation	White (WH)	T-Ambient (Min)	-20 °C
Correlated Color Temperature (Nom)	3000 K	T-Storage (Max)	65 °C
Luminous Efficacy (rated) (Nom)	137.00 lm/W	T-Storage (Min)	-40 °C
Color Consistency	<6	T-Case Maximum (Nom)	70 °C
Color Rendering Index (Nom)	80	Controls and dimming	
LLMF At End Of Nominal Lifetime (Nom)	70 %	Dimmable	No
Operating and electrical		Mechanical and housing	
Input Frequency	50 to 60 Hz	Bulb Finish	Frosted
Power (Rated) (Nom)	14.5 W	Bulb Material	Plastic

T8

Product Length	48 in
Bulb Shape	Tube, double-ended
Approval and application	
Energy Saving Product	Yes
Approbation Marks	RoHS compliance UL certificate DLC compliance
Energy Consumption kWh/1000 h	- kWh
Product data	
Order product name	14.5T8/MAS/48-830/MF20/P 10/1

EAN/UPC - Product	046677557386
Order code	557389
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929002325404
Net Weight (Piece)	0.120 kg
Model Number	9290023254


Dimensional drawing




14.5T8/MAS/48-830/MF20/P 10/1

Product	D1	D2	A1	A2	A3
14.5T8/MAS/48-830/MF20/P 10/1	25.7 mm	28 mm	1198 mm	1205 mm	1212 mm

Photometric data




LEDtube_14.5W_G13_830-GUL




LEDtube_G13_830-POC

Photometric data




LEDtube_G13_1-LDD


Lifetime



LEDtube_70K_1_LumenVsTc-LMP



LEDtube_70K_LifetimeVsTc-LED



LEDtube_70K-LED



LEDtube_70K_FailureRate-LED

T8

Lifetime



LEDtube_70K-LMP

