



T8

12.5T8/COR/48-850/MF18/G 10/1

Our TLEDs are available in InstantFit (Type A / Type C) or MainsFit (Ballast bypass / Type B) versions. The InstantFit lamps work on a broad variety of ballasts and LED drivers. Only InstantFit has over 15,000 lamp & ballast combinations delivering even light output, energy savings and a long lifetime. Our MainsFit products feature a double-ended design, simplifying installation while a proprietary safety circuit minimizes a shock risk. Lamp sizes range from 2-foot to 8-foot and U-bend with a variety of lumen outputs.

Product data

General Information		Input Frequency	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Input Frequency	50 to 60 Hz
Nominal lifetime	50,000 hour(s)	Power Consumption	12.5 W
Switching Cycle	50,000	Lamp Current (Max)	105 mA
Lighting Technology	LED	Lamp Current (Min)	45 mA
EU RoHS compliant	Yes	Wattage Equivalent	32 W
Light Technical		Starting Time (Nom)	0.5 s
Color Code	850 [CCT of 5000K]	Warm-up time to 60% light	0.5 s
Beam Angle (Nom)	240 degree(s)	Power Factor (Fraction)	0.9
Luminous Flux	1,800 lm	Voltage (Nom)	120-277 V
Color Designation	Daylight	UL Type	Type B - bypass the ballast
Correlated Color Temperature (Nom)	5000 K	Temperature	
Luminous Efficacy (rated) (Nom)	144.00 lm/W	Ambient temperature range	-4 °F to 113 °F
Color Consistency	<5	T-Case Maximum (Nom)	140 °F
Color rendering index (CRI)	82	Controls and Dimming	
LLMF At End Of Nominal Lifetime (Nom)	70 %	Dimmable	No
Operating and Electrical		Mechanical and Housing	
Line Frequency	50 to 60 Hz	Bulb Finish	Frosted

T8


Bulb Material	Glass
Product Length	47-1/4 inch
Bulb Shape	Tube, double-ended
Approval and Application	
Energy Saving Product	Yes
Approval Marks	RoHS compliance UL certificate DLC compliance
Energy Consumption kWh/1000 h	- kWh

Product Data

Order product name	12.5T8/COR/48-850/MF18/G 10/1
--------------------	-------------------------------

Full product name	12.5T8/COR/48-850/MF18/G 10/1
Order code	477349
Material Nr. (12NC)	929002394704
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677477349
Numerator - Packs per outer box	10
EAN/UPC - Case	50046677477344


Dimensional drawing




Product

12.5T8/COR/48-850/MF18/G 10/1

Photometric data




General Uniform Lighting - 12.5T8/COR/48-850/MF18/G 10/1





Spectral Power Distribution Colour - 12.5T8/COR/48-850/MF18/G 10/1

Photometric data





Light Distribution Diagram - 12.5T8/COR/48-850/MF18/G 10/1

Lifetime



Life Expectancy Diagram - 12.5T8/COR/48-850/MF18/G 10/1

Life Expectancy Diagram - 12.5T8/COR/48-850/MF18/G 10/1




Lumen Maintenance Diagram - 12.5T8/COR/48-850/MF18/G 10/1

Lumen Maintenance Diagram - 12.5T8/COR/48-850/MF18/G 10/1

T8

Lifetime



Life Expectancy Diagram - 12.5T8/COR/48-850/MF18/G 10/1

