



# **ECO HOME**

# ECOHOME Stick 18W CDL E27 110-127V 1PF/6

Eco Home is the basic energy saver among Philips compact fluorescent lamps, offering great value for money with quality and performance you can trust. It is an ideal high-quality energy-saving replacement for incandescent light bulbs, consuming up to 80% less energy than standard incandescent bulbs and lasting for up to 6 years (based on average residential usage of 1,000 hours a year or 3 hours a day).

#### **Product data**

General Information  Cap-Base E27  Nominal lifetime 8,000 hour(s)  Switching Cycle 5,000  Rated Lifetime (Hours) 8,000 hour(s)  Lighting Technology Compact Fluorescent Integrated  Light Technical  Color Code 865 [CCT of 6500K]  Luminous Flux 1,067 lm  Color Designation Cool Daylight  Chromaticity Coordinate X (Nom) 313  Chromaticity Coordinate Y (Nom) 337  Correlated Color Temperature (Nom) 6500 K  Luminous Efficacy (rated) (Nom) 58 lm/W  Color rendering index (CRI) 80  LLMF At End Of Nominal Lifetime (Nom) 50 %  Operating and Electrical  Line Frequency 50 or 60 Hz		
Nominal lifetime 8,000 hour(s)  Switching Cycle 5,000  Rated Lifetime (Hours) 8,000 hour(s)  Lighting Technology Compact Fluorescent Integrated  Light Technical  Color Code 865 [CCT of 6500K]  Luminous Flux 1,067 lm  Color Designation Cool Daylight  Chromaticity Coordinate X (Nom) 313  Chromaticity Coordinate Y (Nom) 337  Correlated Color Temperature (Nom) 6500 K  Luminous Efficacy (rated) (Nom) 58 lm/W  Color rendering index (CRI) 80  LLMF At End Of Nominal Lifetime (Nom) 50 %  Operating and Electrical  Line Frequency 50 or 60 Hz	General Information	
Switching Cycle 5,000  Rated Lifetime (Hours) 8,000 hour(s)  Lighting Technology Compact Fluorescent Integrated  Light Technical  Color Code 865 [CCT of 6500K]  Luminous Flux 1,067 lm  Color Designation Cool Daylight  Chromaticity Coordinate X (Nom) 313  Chromaticity Coordinate Y (Nom) 337  Correlated Color Temperature (Nom) 6500 K  Luminous Efficacy (rated) (Nom) 58 lm/W  Color rendering index (CRI) 80  LLMF At End Of Nominal Lifetime (Nom) 50 %  Operating and Electrical  Line Frequency 50 or 60 Hz	Cap-Base	E27
Rated Lifetime (Hours) 8,000 hour(s)  Lighting Technology Compact Fluorescent Integrated  Light Technical  Color Code 865 [CCT of 6500K]  Luminous Flux 1,067 lm  Color Designation Cool Daylight  Chromaticity Coordinate X (Nom) 313  Chromaticity Coordinate Y (Nom) 337  Correlated Color Temperature (Nom) 6500 K  Luminous Efficacy (rated) (Nom) 58 lm/W  Color rendering index (CRI) 80  LLMF At End Of Nominal Lifetime (Nom) 50 %  Operating and Electrical  Line Frequency 50 or 60 Hz	Nominal lifetime	8,000 hour(s)
Light Technical  Color Code 865 [CCT of 6500K]  Luminous Flux 1,067 lm  Color Designation Cool Daylight  Chromaticity Coordinate X (Nom) 313  Chromaticity Coordinate Y (Nom) 337  Correlated Color Temperature (Nom) 6500 K  Luminous Efficacy (rated) (Nom) 58 lm/W  Color rendering index (CRI) 80  LLMF At End Of Nominal Lifetime (Nom) 50 %  Operating and Electrical  Line Frequency 50 or 60 Hz	Switching Cycle	5,000
Light Technical  Color Code 865 [CCT of 6500K]  Luminous Flux 1,067 lm  Color Designation Cool Daylight  Chromaticity Coordinate X (Nom) 313  Chromaticity Coordinate Y (Nom) 337  Correlated Color Temperature (Nom) 6500 K  Luminous Efficacy (rated) (Nom) 58 lm/W  Color rendering index (CRI) 80  LLMF At End Of Nominal Lifetime (Nom) 50 %  Operating and Electrical  Line Frequency 50 or 60 Hz	Rated Lifetime (Hours)	8,000 hour(s)
Color Code 865 [CCT of 6500K]  Luminous Flux 1,067 lm  Color Designation Cool Daylight  Chromaticity Coordinate X (Nom) 313  Chromaticity Coordinate Y (Nom) 6500 K  Luminous Efficacy (rated) (Nom) 58 lm/W  Color rendering index (CRI) 80  LLMF At End Of Nominal Lifetime (Nom) 50 %  Operating and Electrical  Line Frequency 50 or 60 Hz	Lighting Technology	Compact Fluorescent Integrated
Color Code 865 [CCT of 6500K]  Luminous Flux 1,067 lm  Color Designation Cool Daylight  Chromaticity Coordinate X (Nom) 313  Chromaticity Coordinate Y (Nom) 6500 K  Luminous Efficacy (rated) (Nom) 58 lm/W  Color rendering index (CRI) 80  LLMF At End Of Nominal Lifetime (Nom) 50 %  Operating and Electrical  Line Frequency 50 or 60 Hz		
Luminous Flux  1,067 lm  Color Designation  Cool Daylight  Chromaticity Coordinate X (Nom)  313  Chromaticity Coordinate Y (Nom)  337  Correlated Color Temperature (Nom)  6500 K  Luminous Efficacy (rated) (Nom)  58 lm/W  Color rendering index (CRI)  80  LLMF At End Of Nominal Lifetime (Nom)  50 %  Operating and Electrical  Line Frequency  50 or 60 Hz	Light Technical	
Color Designation Cool Daylight Chromaticity Coordinate X (Nom) 313 Chromaticity Coordinate Y (Nom) 337 Correlated Color Temperature (Nom) 6500 K Luminous Efficacy (rated) (Nom) 58 lm/W Color rendering index (CRI) 80 LLMF At End Of Nominal Lifetime (Nom) 50 %  Operating and Electrical Line Frequency 50 or 60 Hz	Color Code	865 [CCT of 6500K]
Chromaticity Coordinate X (Nom) 313  Chromaticity Coordinate Y (Nom) 337  Correlated Color Temperature (Nom) 6500 K  Luminous Efficacy (rated) (Nom) 58 lm/W  Color rendering index (CRI) 80  LLMF At End Of Nominal Lifetime (Nom) 50 %  Operating and Electrical  Line Frequency 50 or 60 Hz	Luminous Flux	1,067 lm
Chromaticity Coordinate Y (Nom) 337  Correlated Color Temperature (Nom) 6500 K  Luminous Efficacy (rated) (Nom) 58 lm/W  Color rendering index (CRI) 80  LLMF At End Of Nominal Lifetime (Nom) 50 %  Operating and Electrical  Line Frequency 50 or 60 Hz	Color Designation	Cool Daylight
Correlated Color Temperature (Nom) 6500 K  Luminous Efficacy (rated) (Nom) 58 lm/W  Color rendering index (CRI) 80  LLMF At End Of Nominal Lifetime (Nom) 50 %  Operating and Electrical  Line Frequency 50 or 60 Hz	Chromaticity Coordinate X (Nom)	313
Luminous Efficacy (rated) (Nom) 58 lm/W  Color rendering index (CRI) 80  LLMF At End Of Nominal Lifetime (Nom) 50 %  Operating and Electrical  Line Frequency 50 or 60 Hz	Chromaticity Coordinate Y (Nom)	337
Color rendering index (CRI) 80  LLMF At End Of Nominal Lifetime (Nom) 50 %  Operating and Electrical  Line Frequency 50 or 60 Hz	Correlated Color Temperature (Nom)	6500 K
Coperating and Electrical Line Frequency 50 or 60 Hz	Luminous Efficacy (rated) (Nom)	58 lm/W
Operating and Electrical Line Frequency 50 or 60 Hz	Color rendering index (CRI)	80
Line Frequency 50 or 60 Hz	LLMF At End Of Nominal Lifetime (Nom)	50 %
Line Frequency 50 or 60 Hz		
	Operating and Electrical	
Input Frequency 50 or 60 Hz	Line Frequency	50 or 60 Hz
input i requeity	Input Frequency	50 or 60 Hz


Power Consumption	18.0 W	
Lamp Current (Nom)	245 mA	
Starting Time (Nom)	0.3 s	
Power Factor (Fraction)	0.55	
Voltage (Nom)	110-127 V	
Controls and Dimming		
Dimmable	No	
Mechanical and Housing		
Bulb Shape	Stick	
Approval and Application		
Mercury (Hg) Content (Max)	2 mg	
Energy Consumption kWh/1000 h	18 kWh	
Product Data		
Order product name	ECOHOME Stick 18W CDL E27 110-127V 1PF/6	
Full product name	ECOHOME Stick 18W CDL E27 110-127V 1PF/6	
Full product code	871829165077500	
Order code	929689013802	

Datasheet, 2023, December 19 data subject to change

## **ECO HOME**

Material Nr. (12NC)	929689013802
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291650775
Numerator - Packs per outer box	6

### Dimensional drawing



Product	D (max)	C (max)	F (max)
ECOHOME Stick 18W CDL E27 110-127V 1PF/6	36.0 mm	143 mm	48.4 mm

