



# **Tornado T2**

## Tornado T2 8W CDL E14 220-240V 1PF/6

Tornado has outstanding brightness which makes your colors appear more Vivid. It fits everywhere due to its compact design With comprehensive product range, it allows easy replacement of incandescent lamps all the way

### **Warnings and Safety**

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

#### **Product data**

General Information		
Cap-Base	E14 [E14]	
Nominal lifetime	10,000 hour(s)	
Switching Cycle	10,000	
Rated Lifetime (Hours)	10,000 hour(s)	
Lighting Technology	Compact Fluorescent Integrated	
Light Technical		
Color Code	865 [CCT of 6500K]	
Luminous Flux	475 lm	
Color Designation	Cool Daylight	
Chromaticity Coordinate X (Nom)	313	
Chromaticity Coordinate Y (Nom)	337	
Correlated Color Temperature (Nom)	6500 K	
Luminous Efficacy (rated) (Nom)	59 lm/W	
Color rendering index (CRI)	80	

LLMF At End Of Nominal Lifetime (Nom)	65 %	
Operating and Electrical		
Line Frequency	50 or 60 Hz	
Input Frequency	50 or 60 Hz	
Power Consumption	8.0 W	
Lamp Current (Nom)	60 mA	
Starting Time (Nom)	0.3 s	
Warm-up time to 60% light	5-40 s s	
Power Factor (Fraction)	0.6	
Voltage (Nom)	220-240 V	
Controls and Dimming		
Dimmable	No	


Datasheet, 2023, September 4 data subject to change

## **Tornado T2**

Mechanical and Housing			
Bulb Shape	Spiral		
Approval and Application			
Mercury (Hg) Content (Max)	2.0 mg		
Mercury (Hg) Content (Nom)	1.5 mg		
Energy Consumption kWh/1000 h	8 kWh		
Product Data			
Order product name	Tornado T2 8W CDL E14 220-240V 1PF/6		

Full product name	Tornado T2 8W CDL E14 220-240V 1PF/6		
Full product code	871829111712400		
Order code	929689134401		
Material Nr. (12NC)	929689134401		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	8718291117124		
Numerator - Packs per outer box	6		
EAN/UPC - Case	8718291117131		

## Dimensional drawing



Product	D (max)	C (max)	F (max)
Tornado T2 8W CDL E14 220-240V 1PF/6	47.5 mm	96.5 mm	40.5 mm

