



# Softone ESaver Candle

# Softone Candle 5W WW E14 220-240V 1PF/6

Elegant Energy saving lamp with decorative comfort & design, allows easy replacement of most candle shape incandescent lamp.

### Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

### **Product data**

General Information		
Cap-Base	E14 [E14]	
Nominal lifetime	10,000 hour(s)	
Switching Cycle	30,000	
Rated Lifetime (Hours)	10,000 hour(s)	
Lighting Technology	Compact Fluorescent Integrated	
Light Technical		
Color Code	827 [CCT of 2700K]	
Luminous Flux	190 lm	
Color Designation	Warm White (WW)	
Chromaticity Coordinate X (Nom)	463	
Chromaticity Coordinate Y (Nom)	420	
Correlated Color Temperature (Nom)	2700 K	
Luminous Efficacy (rated) (Nom)	38 lm/W	
Color rendering index (CRI)	82	

	CF 0/
LLMF At End Of Nominal Lifetime (Nom)	65 %
Operating and Electrical	
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Power Consumption	5.0 W
Lamp Current (Nom)	40 mA
Starting Time (Nom)	1.5 s
Power Factor (Fraction)	0.6
Voltage (Nom)	220-240 V
Controls and Dimming	
Dimmable	No


Datasheet, 2023, September 4 data subject to change

# **Softone ESaver Candle**

Mechanical and Housing		
Bulb Shape	B39 [B 39mm]	
Approval and Application		
Mercury (Hg) Content (Max)	2.0 mg	
Mercury (Hg) Content (Nom)	1.5 mg	
Energy Consumption kWh/1000 h	5 kWh	
Product Data		
Order product name	Softone Candle 5W WW E14 220-240V 1PF/6	

Full product name	Softone Candle 5W WW E14 220-240V 1PF/6		
Full product code	871016340524700		
Order code	929689139106		
Material Nr. (12NC)	929689139106		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	8710163405247		
Numerator - Packs per outer box	6		
EAN/UPC - Case	8718291681526		

# Dimensional drawing



Product	D (max)	C (max)	F (max)
Softone Candle 5W WW E14 220-240V 1PF/6	40.5 mm	107.5 mm	39 mm

