


# Tornado T2

## Tornado T2 8y 20W WW E27 220-240V 1CT/12

Tornado has outstanding brightness which makes your colors appear more Vivid. It fits everywhere due to its compact design With comprehensive product range, it allows easy replacement of incandescent lamps all the way

### Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

### Product data

| General Information | |
|---|---|
| **Cap-Base** | E27 [E27] |
| **Nominal lifetime** | 8,000 hour(s) |
| **Switching Cycle** | 5,000 |
| **Rated Lifetime (Hours)** | 8,000 hour(s) |
| **Lighting Technology** | Compact Fluorescent Integrated |

| Light Technical | |
|---|---|
| **Color Code** | 827 [CCT of 2700K] |
| **Luminous Flux** | 1,250 lm |
| **Color Designation** | Warm White (WW) |
| **Chromaticity Coordinate X (Nom)** | 463 |
| **Chromaticity Coordinate Y (Nom)** | 420 |
| **Correlated Color Temperature (Nom)** | 2700 K |
| **Luminous Efficacy (rated) (Nom)** | 65 lm/W |
| **Color rendering index (CRI)** | 82 |

| | |
|---|---|
| **LLMF At End Of Nominal Lifetime (Nom)** | 70 % |

| Operating and Electrical | |
|---|---|
| **Line Frequency** | 50 or 60 Hz |
| **Input Frequency** | 50 or 60 Hz |
| **Power Consumption** | 20 W |
| **Lamp Current (Nom)** | 150 mA |
| **Starting Time (Nom)** | 0.3 s |
| **Power Factor (Fraction)** | 0.6 |
| **Voltage (Nom)** | 220-240 V |

| Controls and Dimming | |
|---|---|
| **Dimmable** | No |

| Mechanical and Housing | |
|---|---|
| **Bulb Shape** | Spiral |


# Tornado T2

| Approval and Application | |
|---|---|
| **Mercury (Hg) Content (Nom)** | 1.5 mg |
| **Energy Consumption kWh/1000 h** | 20 kWh |

| Product Data | |
|---|---|
| **Order product name** | Tornado T2 8y 20W WW E27 220-240V 1CT/12 |
| **Full product name** | Tornado T2 8y 20W WW E27 220-240V 1CT/12 |
| **Full product code** | 871829166296900 |

| | |
|---|---|
| **Order code** | 929689848313 |
| **Material Nr. (12NC)** | 929689848313 |
| **Numerator - Quantity Per Pack** | 1 |
| **EAN/UPC - Product/Case** | 8718291662969 |
| **Numerator - Packs per outer box** | 12 |
| **EAN/UPC - Case** | 8718291662976 |

## Dimensional drawing




| Product | D (max) | C (max) | F (max) |
|---|---|---|---|
| Tornado T2 8y 20W WW E27 220-240V 1CT/12 | 56.5 mm | 111.5 mm | 47 mm |

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.