



SL-23 Composite Inground

Inground, composite, LED, 120V/208V/240V/277V

Inground, composite, LED, 120V/208V/240V/277V - 101 lm/W

The SL-23 is an inground commercial luminaire manufactured from compression molded Rhinolite Composite housing, corrosion resistant in harsh lighting environments. Supplied with two 3/4" NPT conduit entrances and separated from the lamp compartment by the anti-wicking chamber that is hermetically sealed. The ballast compartment is sealed and also separated from the lamp compartment by another anti-wicking chamber. Applications include landscape lighting, architectural lighting, trees, flagpoles, columns, building accents and wallwashing.

Product data

General Information		Efficacy	
Lamp Source Code	LED	101 lm/W	
Lamp Watts	11		
Number of Lamps	1		
Color Temperature	4000K		
Mounting	In Ground		
Operating and Electrical		Product Data	
Voltages	120/208/240/277 V	Order product name	Inground, composite, LED, 120V/208V/240V/277V
		Commercial Code	SL-23-LED
		Order code	SL-23-LED
		Catalog Number Description	Inground, composite, LED, 120V/208V/240V/277V
		Service / Spec Smart	-
		Material Nr. (12NC)	HAD30000002
Initial Performance (IEC Compliant)			
Luminaire Lumens	1156		