



# MicroSquare gen2 Suspended LED

MicroSquare gen2 Suspended Indirect/Direct LED,  
5900 lm/4ft, 3000/3500/4000K Indirect/Direct, Flush Silk  
Lens Down - Asymmetric Wide-Throw Lens Up

MicroSquare gen2 Suspended Indirect/Direct LED, 5900 lm/4ft,  
3000/3500/4000K Indirect/Direct, Flush Silk Lens Down - Asymmetric  
Wide-Throw Lens Up - 113 lm/W

Philips Ledalite's MicroSquare gen2 has been re-engineered to furnish your space with the highest quality, discreet, narrow lines of continuous light. Elegant, low glare illumination with wide-throw upper and lower distributions improve visual comfort while allowing increased fixture spacing. This in turn, helps reduce initial and operating costs.

## Product data

General Information	
Lamp Source Code	LED
Colour Temperature	3000/3500/4000K
CRI	80
Photometric Distribution Type	Direct/Indirect
Mounting	Suspended
Operating and Electrical	
Luminaire Input Watts	49.1
Voltages	120/277/347 V

Mechanical and Housing	
Shape	Linear
Initial Performance (IEC Compliant)	
Luminaire Lumens	5900
Efficacy	113 lm/W
Product Data	
Order product name	MicroSquare gen2 Suspended Indirect/Direct LED, 5900 lm/4ft, 3000/3500/4000K Indirect/Direct, Flush Silk Lens Down - Asymmetric Wide-Throw Lens Up
Commercial Code	2205LxBLW
Order code	2205LxBLW

# MicroSquare gen2 Suspended LED

Catalog Number	Description
	MicroSquare gen2 Suspended Indirect/Direct LED, 5900 lm/4ft, 3000/3500/4000K Indirect/Direct, Flush Silk Lens Down - Asymmetric Wide-Throw Lens Up
Service / Spec Smart	-

Material Nr. (12NC)	LED04280
---------------------	----------

