



SlimSurface LED Downlight

SlimSurface LED downlight, 5-inch round, surface mount, 80 CRI, 2700K CCT, 650 lm, 120V, Standard (TRIAC) dimming, wet location, Matte White finish

SlimSurface LED downlight, 5-inch round, surface mount, 80 CRI, 2700K CCT, 650 lm, 120V, Standard (TRIAC) dimming, wet location, Matte White finish

SlimSurface LED is a low profile downlight intended for ceiling or wall mount applications. This 0.625" thick luminaire offers the appearance of a recessed downlight but is actually surface mounted.

Product data

General Information		Shape	
Lamp Source Code	LED	Round	
Colour Temperature	2700K		
CRI	80	Initial Performance (IEC Compliant)	
Downlight Type	Open Downlight	Luminaire Lumens	
Photometric Distribution Type	Direct	650	
Mounting	Surface Wall		
Operating and Electrical		Product Data	
Luminaire Input Watts	10	Order product name	
Voltages	120 V	SlimSurface LED downlight, 5-inch round, surface mount, 80 CRI, 2700K CCT, 650 lm, 120V, Standard (TRIAC) dimming, wet location, Matte White finish	
Mechanical and Housing		Commercial Code	
Aperture Size Code	5 in	S5R827K7	
		Order code	
		S5R827K7	
		Catalog Number Description	
		SlimSurface LED downlight, 5-inch round, surface mount, 80 CRI, 2700K CCT, 650 lm, 120V, Standard (TRIAC) dimming, wet location, Matte White finish	

SlimSurface LED Downlight

Service / Spec Smart	Service Smart (2 Days) USA
Material Nr. (12NC)	LIGU60011110

